
TWILIGHT - model: WS-W55

LED Outdoor









Shown without
decorative trellis element

P	R	o	D	U	C	Г	DE	S	CI	RI	P	Т	I	0	N	l
---	---	---	---	---	---	---	----	---	----	----	---	---	---	---	---	---

Waning light of day through the trees. Indirect LED illumination behind a lattice screen gives the illusion of twilight. Glare free illumination with ambient and down lighting for safety, security and architectural accent.

FEATURES

- IP65 rated Wet location listed
- ETL & cETL listed
- ADA compliant, low profile design
- Removable cage bars element
- Replaceable LED module
- No transformer or driver required
- 80,000 hour rated lifeColor Temp: 3000K
- CRI: 90

SPECIFICATIONS

Construction: Aluminum

Light Source: High output LED

Dimming: Dims to 10% with an electronic low voltage (ELV) dimmer

Mounting: Mounts directly to junction box

Fixture Type:

Project:

Location:

Catalog Number:

Finish: Bronze (BZ)

ORDER NUMBER

Model	Heig	ght	Width	Watt	Voltage	LED Lumens	Delivered Lumens	Fini	sh
WS-W55	16 21	16" 21"	7" 9"	25W 28W	120V 120V	1060 1240	626 768	BZ	Bronze

Back Plate Dimensions:

Model	Dimension
WS-W5516	4%L x 4%W x 1%H
WS-W5521	4¾L x 4¾W x 1¾H

WS-W55 - BZ

Example: WS-W5516-BZ