

3" GIMBAL LED DOWNLIGHT BEAM DEGREE ADJUSTABLE



Features

- » Super bright sleek downlight
- » 360° gimbal rotation
- » Beam angle adjustable 20 - 40°
- » Simple installation
- » Dimmable
- » Low clearance applications
- » Hardwire junction box
- » Patent pending

Applications

- » Downlighting
- » Soffit lighting
- » Low clearance lighting
- » Architectural

Dimmable | IC & Damp Location Rated

3" Gimbal LED Downlight | Adjustable Beam Angle

**IC & DAMP
LOCATION RATED**



Product Code	ALED - RD01G	Color Temperature	WW 2700K / 3000K / 4000K / CW 5000K / (RGBW - 24V DC)
Voltage	120V AC (12V DC available)	Lumens	775
Wattage	8W	Beam Degree	Adjustable from 20 to 40°
Trim Dimensions	3 ^{11/32} " (85mm)	Hole Cutout	Ø2 ^{3/4} " (70mm)
Trim Colors	Brushed Nickel, Black, White	Housing	Aluminum

Includes Light Engine & Dimmable Driver

::: Light Engine :::

::: Trim Style :::

Trim Color

Product Ordering Code



Round

xx = Color Temperature



Brushed Nickel (BN)
Black (BK)
White (WT)

ALED-RD01G-BN-XX
ALED-RD01G-BK-XX
ALED-RD01G-WT-XX

Square



Brushed Nickel (BN)
Black (BK)
White (WT)

ALED-SQ01G-BN-XX
ALED-SQ01G-BK-XX
ALED-SQ01G-WT-XX