



[Search products](#)

[HOME](#) > [PRODUCTS](#) > [NORTH AMERICA](#) > [Highbay](#) > **160W Annulight™ INDUSTRIAL LED LIGHT FIXTURES WITH MOTION SENSOR**

160W ANNULIGHT™ INDUSTRIAL LED LIGHT FIXTURES WITH MOTION SENSOR

Kinglumi delivers energy efficient industrial lighting solutions with Annulight™ wide range of industrial LED light fixtures featuring smart lighting control and management. There is built-in 360-degree motion sensor included in such ODM LED industrial lights to turn on/off lights automatically and adjusting the lighting brightness levels based on the changes of surrounding moving objects. Such Smart lighting control system is able to reduce power use and electricity costs to a large extent, together with helping making contributions to cutting down carbon emissions and building green environments.

The energy efficacy of Annulight™ high bay with motion sensor reach up to 130 lumen per watt, helpful to deliver adequate light levels over large and spacious space while keeping power consumptions to minimum level. Besides, they are designed both non-dim and versatile dimming solutions ranging from DALI, 1-10V to motion sensor option, essential for adapting the needs of lighting design for wide huge selection of applications. If you want to install light fixtures freely depending on specific installation environments, these industrial high bay light fittings from China are the perfect choice as they can be well placed in surface, suspension, hook mounted as well as wall mounting ways.



Base (standard designation):

[DOWNLOAD](#)

[CLICK TO PRINT PAGE](#)

FEATURES:

- Turn on/off lights as well as adjusting the lighting brightness with smart occupancy sensor lighting system
- Awesome light efficacy of 130LM/W is provided to deliver adequate light output while saving tremendous power
- High quality punching aluminum heat-sink is presented to ensure continuous conductive heat transfer, crucial for improving lifespan and maintaining durable light fixtures
- Presented to achieve full light output instantly without warm-up process after opening
- Surface-mounted, suspension mounting, hook mounting as well as wall mounting solutions are available
- Adapting to the requirements of various lighting distributions with multiple wide beam angles including 60° , 80° to 110° .
- Equipped with excellent and patented anti-glare reflectors and original Samsung LEDs to achieve perfect lighting effects.
- Color temperatures of 2700K,3000k,3500k,4000k,5000k are presented to meet the needs of different lighting atmospheres.
- Approved by CE,Rohs, SAA, ETL,DLC,FCC institutes. safely applied around the world for a variety of scenarios

Annulight™
LED high bay

DELIVER ENERGY EFFICIENT INDUSTRIAL LIGHTING SOLUTIONS WITH ANNULIGHT™ RANGE OF LED HIGH BAY LIGHTS

Contact us via sales@kinglumi.com to learn more details

K&L

DALI, 1-10V Dimming options

85-230W available

11000-30000LM light output

Motion sensor is available

Beam angles of 60, 80 and 110 degrees

DESIGNED WITH BUILT-IN MOTION SENSOR

Annulight™
MOTION OCCUPANCY LED HIGH BAY

MOTION SENSOR ATTRIBUTES
Control signal: Microwave/Radar 5.8GHz
Detection angle: 360°
Detection height: 1.2M
Standby power: 0.5W

Hold on time
Hold on time setting: 0.5, 30.5, 1.205, 3.005, etc
Hold on brightness setting: 10%, 20%, 30%, 50%

1.75M

Brightness detection: 0%-100% time: 1 S

Radar detection area

Radar detection area

Detection speed: >1m/s
(1m/s will delay the detection sensitivity)

Detection Distance: 5

Detection Distance: 5

Detection speed: >1m/s

H(m)	4	5	6	7	8	9	10	11	12
S(m)	5.3	5.8	6	5.5	5	4.5	4	2.5	1.4

H(m): high bay installation height
S: (m): Detection distance

K&L

OFFERED WITH VARIOUS WIDE BEAM ANGLES

Interchangeable Reflectors

110°UGR 26

80°UGR 18

60°UGR 14

COME WITH HUGE SELECTION OF WATTS AND SOLUTIONS

ANNULIGHT™ HIGH BAY OPTIONS

K&L Code	Power(W)	Lumen(lm)	Fa	Beam Angle(°)	Dimming	Finish	DxH(mm)
KL-HB-012.V01	85	11000	82	60, 80, 110	Non-dim	BK	399x193
KL-HB-011.V02	125	16000	82	60, 80, 110	Non-dim	BK	399x193
KL-HB-010.V02	155	20000	82	60, 80, 110	Non-dim	BK	399x193
KL-HB-010.V24	200	25000	82	60, 80, 110	Non-dim	BK	399x193
KL-HB-013.V01	230	30000	82	60, 80, 110	Non-dim	BK	399x193
KL-HB-012.V05	88	11000	82	60, 80, 110	DALI	BK	399x193
KL-HB-011.V05	130	16000	82	60, 80, 110	DALI	BK	399x193
KL-HB-010.V12	160	20000	82	60, 80, 110	DALI	BK	399x193
KL-HB-010.V25	200	25000	82	60, 80, 110	DALI	BK	399x193
KL-HB-012.V06	88	11000	82	60, 80, 110	1-10V	BK	399x193
KL-HB-011.V06	130	16000	82	60, 80, 110	1-10V	BK	399x193
KL-HB-010.V14	160	20000	82	60, 80, 110	1-10V	BK	399x193
KL-HB-012.V07	88	11000	82	60, 80, 110	Motion Sensor	BK	399x193
KL-HB-011.V08	130	16000	82	60, 80, 110	Motion Sensor	BK	399x193
KL-HB-010.V19	160	20000	82	60, 80, 110	Motion Sensor	BK	399x193



NAVIGATION

[PRODUCTS](#)
[DOWNLOAD](#)
[APPLICATIONS](#)
[PROJECTS](#)
[NEWS](#)
[CONTACT](#)
[ABOUT](#)

CONTACT US

TEL : +86-755-2951 6789
FAX : +86-755-2951 6769
E-mail: sales@kinglumi.com
ADD: Bldg 3,Nangang Third Industrial Zone,Tangtou Shiyan
Town,Baoan District,Shenzhen City,China

FOLLOW

[SEARCH](#)

[Link](#)