

PL-UPD-5X1W-2S | Outdoor LED Up Down Light



Introduction:

This wall sconce is made of high quality aluminum die casting, Surface paint treatment environmentally friendly materials, beautiful and silicone rubber waterproof seal, internal epoxy potting, ensuring superior waterproof lamps performance. High-brightness light source of imported chips, high brightness, low power, low heat, long life reaches 50000H, can be divided into color, colorful discoloration. It is mostly for decoration and sometimes it can be also for lighting. The lamps are sealed extrusion and molded power connections make it resistant to water, dirt and any weather conditions. Consumes up to 15% less energy than traditional one and will quickly pay for itself. Also it is easy to install and anyone can do it, no training or special tools required. Quick mount installation brackets and channels are available for applications.

Specifications:

Item NO.	PL-UPD-5X1W-2
Power	10W
Size	L65*W100*H230mm
LED chip	Epistar
Material	Die-cast aluminum
Light efficiency	80LM/W
Protection level	IP65
Power Factor	0.95
CCT	4000K
Housing color	Black, Gray
Light color	W/WW/Y/R/G/B/Pink in option
Voltage	AC100V~277V
Beam angle	15°/30°/60°/90°
Life span	50,000hrs
Warranty time	3 years for ETL
Certificate	CE, RoHs, ETL and cETL

Features and advantage:


- 1) Two side lighting or one side lighting in option;
- 2) Wide input voltage from AC 100V to AC 277V;
- 3) J-box base fixture which matches with junction box;
- 4) For both commercial lighting and decoration. For decoration it has red, green, blue and RGB changing color;
- 5) With optical lens inside, which can light far on the wall. Can be in different light beam angle in option;
- 6) ETL, cETL, CE, RoHS approval;
- 7) Finish color can be black, bronze, gray, white in option;
- 8) IP65 waterproof. Both indoor and outdoor use;
- 9) Very easy installation with special design, no training or special tools required.

Light Color in option:



Application:

- 1) Hotel; 2) Motel; 3) Building; 4) House; 5) Garden lighting; 6) Column; 7) Area lighting



Warning:

- To prevent personal injury or product damage only licensed electricians should install.
- To avoid electric shock or component damage disconnect power before attempting installation or servicing.
- This product must be installed in accordance with the national electric code (NEC) and all applicable federal, state and local electric codes and safety standards.
- Any alteration or modification of this product is expressly forbidden as it may cause serious personal injury, death, property damage and/or product malfunction.
- To prevent product malfunction and/or electrical shock this product must be properly grounded.
- This luminaire is designed to operate in ambient temperatures ranging from -20°C to 45°C.

Installation:

