

Catalog #		Type
Project		Date
Prepared by		

AFR3G-08

3" Gimbal Round Recessed LED

Recessed Light



DESIGN FEATURES

- Air-tight and damp location approved
- Perfect for limited space locations - only 55mm "thick, Cutout 70mm
- Type IC rated - approved for direct contact with insulation
- Pot light housing is not required even for insulated ceilings
- Isolated driver inside junction box

• Body

- Stamping forming aluminium heat radiation shell

Dimming

- When used with TRIAC dimming controls (Consult factory for compatible dimmers).

Warranty

- 50,000hr of lamp life.

- Listing** - ETL Listed.
- Energy star

SPECIFICATION

LED Quantity	Double Color COBS
Input Voltage	120V AC
Wattage (+/-5%)	8W
Lumen (+/-5%)	700lm
Efficacy(LPW) (+/-5%)	> 85lm/W
CCT Change	27K,30K,35K,40K,50K
CRI (Typical)	> 80
Beam Angle	40° Beam with 38° tilt and 360° rotation
Dimming	Triac
Lamp Life	50,000hr
Environment	Indoor,Damp

120V Approved Dimmers

- * Lutron : TGCL-153PH
: LGCL-153PH
: MACL-153M
: DVCL-153P
: CTCL-153P
- * Leviton: 6672
6674
IPL06
- * Pass&seymour:HCL453P
- * Cooper:SAL06P

Consult tech. service or factory for additional dimmers

Ver:1.0