LED Linear Pendant

START FROM HERE

- Make sure power is completely off at the fuse box.
- · Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area.
- Wear gloves at all times during this installation.
- Read instructions carefully before you start assembly.
- · Keep this instruction sheet for future reference.

Technical Support: 1-855-855-8926

Please Note:

- All Kuzco LED fixture comes with pre-wired LED module(s).
- Unless instructed to do so, please do not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage.
- For dimming, an ELV (Electronic Low Voltage) or TRIAC type of dimmer is required.

Height Adjust (Illustration 2)

- 1. Remove Magnetic Cover Plates (2b)
 - 2. To shorten/lengthen the suspension wire (2c), push/pull the suspension wire (2c) into the canopy. Ensure that the suspension wire (2c) is pushed/pulled on both ends (outside of the canopy (2a) and right before the wire gripper (2d)). There should now be slack suspension wire in front of the wire gripper (2d)
 - **3.** Release the wire gripper (2d) lock by pushing the wire gripper (2d) sleeve in. Then push all remaining slack wire through the wire gripper
 - **4.** Release the wire gripper (2d) sleeve to lock the suspension wire (2c) into place
 - **5.** Repeat for the other end of the pendant

- Remove fixture from its original package
- Separate mounting plate (1c) from canopy (2a) by removing canopy screws (1e) with screwdriver
- **3.** Attach mounting plate (1c) to electrical junction box (1a) using screws provided (1d) in hardware package
- 4. Determine the desired mounting height of the pendant and adjust using the wire gripper inside the canopy (2a) as shown in Illustration 2
- **5.** Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package
- **6.** Attach canopy **(2a)** to mounting plate **(1c)** and secure with screws (1e)

