PANDORA
WS25350

WALL

PROJECT

DESCRIPTION

Dual square profile linear aluminum arms with rectangular wall mount. Inset opal polymeric diffusers. Finely textured plate or powder-coated finish. Wall emitting lights with rotational adjustment.

WS25350-BN
Brushed Nickel

WS25350-BK
Black

WS25350-GD
Gold

WS25350-WH
White



SPECIFICATION DETAILS

* For custom options, consult factory for details.

Fixture Dimensions	W50" x H4-5/8" x E3-7/8"
Light Source	LED
Wattage	35W
Total Lumens	2980lm
Delivered Lumens	BK-800lm*; BN-1410lm*; GD-1160lm*; WH-1630lm*;
Voltage	120V
Color Temperature	3000K
CRI (Ra)	>90
Optional Color Temps	2700K - 5000K Available, Minimum Order Quantities Apply
LED Rated Life	50,000 hours
Dimming	100% - 10%, TRIAC or ELV Dimmer (Not Included)
Diffuser Details	White Acrylic Diffuser
Location	Dry
Warranty	5 Years
ADA Compliant	Yes
Canopy Dimensions	W3" x H5-1/8" x E1-5/8"

KUZCO

19054 28TH AVENUE
SURREY - BC V3Z 6M3
CANADA

WWW.KUZCOLIGHTING.COM

COMMENT

Intertek