

# ASSEMBLY AND INSTALLATION INSTRUCTIONS


**WARNING:** Be sure the electricity to the wires you are working on is shut off, either the fuse is removed or the circuit breaker is shut off.

**NOTE:** Before installing, consult local electrical codes for wiring and grounding requirements.

Carefully remove the fixture from the carton, and check that all parts are included, as shown in figure. Be careful not to misplace any of the screws or parts which are needed for installing the fixture.

## Assembly and Installation Step:

1. Fasten Cross Bar onto Outlet Box using 2 Outlet Box Screws. (Make sure the thread of the mounting screws is facing outside when the Cross Bar is attached to the Outlet Box).
2. Using 2 pliers, twist opens the links at two ends of the Chain. Hook one link to the Loop of the Canopy, and close the link. Hook the other link to the Loop of the fixture, and close the link. Wave the fixture wires up through the chain links, the Loop and the Canopy in the Cross Bar.
3. Connect wires with white to white and black to black, cover the connections by using the Wire Connectors provided. Tie the ground wire from Outlet Box and from fixture to the Ground Screw on the Cross Bar.
4. Fasten the Canopy onto the ceiling using the Lock Nuts provided.
5. Unscrew the Bottom Finial from the Shade. Install candle tube and bulb (Not included) then fasten the Shade onto the Fixture Body by screwing the Finial.
6. Turn on the power.



**522CHM-BK**