



LED Flush Mount (Slim 1 Ring) RGD-FM15/MK/D/1R/BN

LED Slim 1 Ring round ceiling light 15", 5 Multi-K selectable













Features & Benefits

CETL listed, Energy Star
Size 15", CRI >80
5 CCT colour selectable 2700/3000/3500/4000/5000K

L70 @ 50,000 Hrs

TRIAC dimmable

1 Ring Brushed Nickel finish, PMMA Opal lens

Damp location approved



2700K





3000K 3500K 4000K

soft white warm white neutral white cool white





Warranty

5-year limited warranty in commercial use from the date of purchase

Operating temperature range between -20°C and +40°C

5 CCT Colour Selectable

Product Specification


0	rdering Code	Energy Star	Model Number	Description		Input Voltage (V)		Initial Delivered Lumens (lumen)	CRI	Damp Location	M.O.D. (inch)	Case QTY.
3	664156	Υ	RGD-FM15/24W/MK/D/1R/BN	LED Flush Mount 15" 24W Multiple Kelvin 1Brush Nickle Ring	24	120	50,000	1800	80	Υ	15	8

Applications

Bedrooms, living rooms, hallways, kitchens and etc

Dimensional drawing





Ordering Information Example: RGD-FM15/24W/MK/D/1R/BN

Family Name	Fixture Type	Wattage	CCT (Kelvin)	Dimmable	Body	
RGD	FM15	24W	MK	D	1R/BN	
(Rigid)	(LED 15" Flush Mount)		(Multiple Kelvin Selection)	(Dimmable)	(1 Ring Brush Nickel)	