

EASY CONNECT® INSTALLATION INSTRUCTIONS

EW-1 12/12

QUESTIONS OR CONCERNS CONTACT CANARM AT:

1-800-265-1833 (English) • 1-800-567-2513 (French) Monday through Friday 8:00 AM to 5:00 PM E.S.T.




SAFETY PRECAUTIONS:

1.TURN OFF ELECTRICAL POWER BEFORE STARTING INSTALLATION OF LIGHT FIXTURE.


2.THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

NOTE: Product May Not Look Exactly As Shown In Figures.


INSTALL EASY CONNECT MOUNTING BRACKET: **STEP 1**



Attach easy connect mounting bracket to electrical box with electrical box screws (not included).




STEP 2 - Option 1




Connect (push) electrical wires from electric box (house wiring) into correct inserts. Black (Live), White (Neutral), Green (Ground)

Option 2 - MULTIPLE ELECTRICAL BOX WIRES




For multiple black (live) & white (neutral) wires joined in the electrical box (house wiring), attach a single "black" and "white" Jumper Wire before connecting. Strip 7mm from a 6" Jumper Wires (AWG 12-24) supplied. Then connect (push) wires into correct inserts.

CONNECT LIGHT FIXTURE STEP 3




Connect (push) electrical wires from fixture into correct inserts. Black (live), White (neutral), Green (ground)

STEP 4




STYLE#1-Tuck electrical wires into outlet box and position fixture over studs or nipple on mounting bracket assembly. Secure fixture in place with star washer(s) and cap nut(s).

Note: If required, assemble body and spread the arms of the fixture out evenly.



STYLE #2 - Insert one screw into the mounting bracket - do not tighten yet. Tuck electrical wires into outlet box and position fixture over the mounting bracket. Line up the screw in the bracket to the "7" hole on the fixture. Slide fixture to secure in place. Insert remaining screw. Tighten both screws to secure.

STEP 5 - Optional for some models (Note: Refer to the style of assembly that matches the style of your fixture.)



STYLE#1 - Remove spinner nut from socket. Position glass on the fixture and secure with spinner nut. Install proper bulb type and wattage. **Note:** Glass may face up or down.



If your fixture has shades,

STYLE#2A - Remove spinner nut from socket. Position shade on lamp and secure with spinner nut. Place shade on tube, then install bulb.

STYLE#2B - Install bulb, shade then finial.