



MR16 GU10 Base

Ordering Information

Model No.	Item name	Lumens ² (lm)	Watts (w)	CCT ¹ (k)	Efficacy (lm/w)	CRI	Lifetime ³ (h)	Beam Angle	Base type	Voltage (v)	Cerification	Equivalent ⁴ (w)
L6-MR16 GU10D-7W-2700K 25°	MR16	500	7	2700	71	80	25000	25°	GU10	120	UL/CUL, FCC, Energy Star	50
L6-MR16 GU10D-7W-2700K 40°	MR16	500	7	2700	71	80	25000	40°	GU10	120	UL/CUL, FCC	50
L6-MR16 GU10D-7W-3000K 25°	MR16	500	7	3000	71	80	25000	25°	GU10	120	UL/CUL, FCC,	50
L6-MR16 GU10D-7W-3000K 40°	MR16	500	7	3000	71	80	25000	40°	GU10	120	UL/CUL, FCC,	50
L6-MR16 GU10D-7W-4000K 25°	MR16	500	7	4000	71	80	25000	25°	GU10	120	UL/CUL, FCC	50
L6-MR16 GU10D-7W-4000K 40°	MR16	500	7	4000	71	80	25000	40°	GU10	120	UL/CUL, FCC	50

3 THREE YEARS WARRANTY



1. CCT Range complies to ANSI C78.377-2008.

2. Thermally stable typical lumens (± 10%)

3. Rated life is based on 70% lumen maintenance, and engineering testing and probability analysis.

4. Equivalency based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.


5. Energy Star® will be available in May, 2014.

Note: All Information consistent with IESNA LM-80-08 results and IESNA LM-79-08 testing completed by a qualified third party facility.

Note: All lamps meet Energy Star® Program Requirements for Lamps and will be submitted for testing.

Dimensions

Model	MOL	Diameter
MR16 GU10	2.19"	1.97"



Note: Designed to comply with RoHS Directive 2002/95/EC.

Energy Savings

Model No.	Equivalent	Energy Savings
L6-MR16 GU10D-7W-2700K 25°	50W Incandescent	\$118
L6-MR16 GU10D-7W-2700K 40°		
L6-MR16 GU10D-7W-3000K 25°		
L6-MR16 GU10D-7W-3000K 40°		
L6-MR16 GU10D-7W-4000K 25°		
L6-MR16 GU10D-7W-4000K 40°		

*Actual Equivalent Replacement, based on the Energy Star® Integral LED Lamp Center Beam Intensity Benchmark Tool.

Note: Energy Savings based on using one bulb for 25,000 hr rated life at 11¢/kWh. Does not include maintenance and replacement lamp savings.