

Project:			
Fixture Type:			
Location:			
Contact:			

LED Bulkheads

Wall or ceiling mounted • Wet location listed PROGRESS LED



Description:

One-Light 9-1/2" LED Wall or Ceiling Bulkhead. General purpose LED luminaire comprised of a diecast aluminum frame and polycarbonate diffuser. Fixtures are impact resistant and can be mounted on wall or ceiling. Replaceable LED module. White finish.

Specifications:

- White (-30) (powder coat paint)
- Aluminum Construction
- White polycarbonate diffuser
- · LED Module is replaceable (part # 93053641;)
- Robust and energy efficient.
- Offers various mounting options.
- Can be widely adapted for indoor and outdoor applications.
- Meets California Title 24 high efficacy requirements for outdoor use only.
- · 1,211 lumens 71.2 lumens/watt per module (source)
- · 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- · ENERGY STAR® qualified
- · Meets California Title 24 high efficacy requirements for outdoor use only

P3648-3030K9

Images:



Performance:

Number of Modules	1
Input Power	17w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1211/71.2 (LM-82)
Lumens/LPW (Delivered)	1107/64.4 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR® qualified
	Meets California Title 24 high efficacy requirements
	for outdoor use only

Dimensions:

Diameter: 9-1/2" Depth: 4-1/2" Height: 9-1/2" H/CTR: 4-9/16"

Glass Width: 9-3/16" Length: 9-3/16" Height: 3-5/8"



LED Bulkheads





P3648-3030K9

Dimming Notes:

P3648 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron	Nova T NTELV-300
Lutron	Vierti VTELV-600
Lutron	Maestro MAELV-600
Lutron	spacer/system SPSELV-600
Leviton	Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.