

Project:

Fixture Type:

Location

Contact:

Drums And Clouds

Flush-Mount Mounted • Damp Location Listed PROGRESS LED



Description:

LED flush mount with white acrylic diffuser mounts to baked enamel ceiling pan. Twist on installation with a single locking thumb screw. UL approved for damp locations. Ceiling or wall mount. 3000 lumens, 93.8 lumens/watt (delivered), 3000K and 90CRI. ENERGY STAR and Title 24.

Specifications:

- White acrylic Diffuser
- White acrylic diffuser
- Twist on installation.
- Wall or ceiling mount
- \cdot White finish
- 3000 lumens, 93.8/lumens per watt (delivered)
- 3000K color temperature, 90+ CRI
- Damp location listed
- Dimmable to 10% with many Forward Phase (Triac) or Electronic Low Voltage (ELV) dimmers
- Energy Star Qualified
- Meets California T24 JA8-2016.
- Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" recessed outlet box: 16.125 in W., 0.8125 in ht., 16.125 in depth
- Mounting strap for outlet box included
- 6 in of wire supplied

Performance:

| Number of Modules | 1 |
|------------------------|------------------------------------|
| Input Power | 32 W |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Delivered) | 3,000/93.8 (LM-79) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 36000 (L70/TM-21) |
| EMI/RFI | FCC Title 47, Part 15, Class B |
| Max. Operating Temp | 30°C |
| Warranty | 5-year Limited Warranty |
| Labels | ETL Damp Location Listed |
| | ENERGY STAR [®] qualified |
| | Meets California Title 24 JA8-2016 |




P730003-030-30

Dimensions:

Diameter: 16-15/16 in Height: 4-1/8 in

White acrylic Diffuser Width: 16-15/16 in Height: 3-13/16 in





Drums And Clouds

Flush-Mount Mounted • Damp Location Listed PROGRESS LED



 $\mathsf{P730003}\text{-}30\text{-}30$ is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

| Lutron_Nova T VTELV-300 |
|---------------------------|
| Lutron_Diva DVELV-300P |
| Lutron_Diva DVCL-253P |
| Lutron_Caseta Wireless |
| Lutron_Toggler TGCL-153PH |
| Lutron_Ariadni AYCL-153P |
| Lutron_NTLV-600P |
| Lutron_NAELV-601 |
| Lutron_Nova N-600 |
| Leviton_SureSlide 6674 |
| Leviton_AWSMT-EAW |
| |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P730003-030-30