


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:12.00V I:0.9631A P:11.56W PF:1.0000 Lamp Flux:319.064x1 lm		
NAME: LED Strip	TYPE:Indoor lighting	WEIGHT:
SPEC.:5050RGB 60LED	DIM.: 1000*10*1MM	SERIAL No.:201511104
MFR.:	SUR.:1000*10mm	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 27.60 lm/W			
MODEL:02T50XX060B-12(WCP)-10		Imax(cd)	101.5	S/MH(C0/180)	1.36
NOMINAL POWER(W)	11.5	LOR(%)	100.0	S/MH(C90/270)	1.40
RATED VOLTAGE(V)	DC 24	TOTAL FLUX(lm)	319.06	η UP,DN(C0-180)	0.0,47.7
NOMINAL FLUX(lm)	319.064	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,52.3
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	24	η down(%)	100.0	CIBSE SHR MAX	1.50

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:4.950m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM


ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	98.68	97.79	97.85	99.57	101.2	101.0	100.7	100.4	0- 10	9.556	9.556	3,3
20	93.74	93.13	93.85	95.91	98.42	99.04	98.60	97.35	10- 20	27.74	37.30	11.7,11.7
30	86.19	86.28	87.30	89.88	92.93	94.39	93.83	91.38	20- 30	43.16	80.45	25.2,25.2
40	76.15	76.99	78.34	80.94	84.73	86.92	86.38	82.70	30- 40	54.01	134.5	42.1,42.1
50	63.31	65.13	66.52	68.92	73.31	76.05	75.89	69.96	40- 50	58.79	193.2	60.6,60.6
60	46.58	49.19	50.64	52.30	57.17	59.98	60.41	53.82	50- 60	55.70	249.0	78,78
70	26.57	29.57	30.95	31.37	36.19	38.59	39.47	33.33	60- 70	43.32	292.3	91.6,91.6
80	6.685	9.549	10.13	9.318	13.34	13.97	15.20	11.50	70- 80	23.29	315.6	98.9,98.9
90	0	0	0	0	0	0	0	0	80- 90	3.502	319.1	100,100
100	0	0	0	0	0	0	0	0	90-100	0	319.1	100,100
110	0	0	0	0	0	0	0	0	100-110	0	319.1	100,100
120	0	0	0	0	0	0	0	0	110-120	0	319.1	100,100
130	0	0	0	0	0	0	0	0	120-130	0	319.1	100,100
140	0	0	0	0	0	0	0	0	130-140	0	319.1	100,100
150	0	0	0	0	0	0	0	0	140-150	0	319.1	100,100
160	0	0	0	0	0	0	0	0	150-160	0	319.1	100,100
170	0	0	0	0	0	0	0	0	160-170	0	319.1	100,100
180	0	0	0	0	0	0	0	0	170-180	0	319.1	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
 Humidity:65.0%
 Test Distance:4.950m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES




C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 4.950m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.04	.00	.96	1.02	.98	.94	.97	.94	.91	.93	.91	.88	.90	.88	.86	.84
2.0	.90	.83	.77	.88	.82	.76	.85	.79	.75	.81	.77	.73	.78	.75	.71	.69
3.0	.79	.70	.64	.77	.69	.63	.74	.67	.62	.71	.66	.61	.69	.64	.60	.58
4.0	.69	.60	.54	.68	.60	.53	.66	.58	.52	.63	.57	.52	.61	.56	.51	.49
5.0	.62	.53	.46	.61	.52	.46	.58	.51	.45	.56	.50	.44	.55	.49	.44	.42
6.0	.55	.46	.40	.54	.46	.40	.53	.45	.39	.51	.44	.39	.49	.43	.38	.36
7.0	.50	.41	.35	.49	.41	.35	.48	.40	.34	.46	.39	.34	.45	.39	.34	.32
8.0	.46	.37	.31	.45	.37	.31	.44	.36	.31	.42	.35	.30	.41	.35	.30	.28
9.0	.42	.33	.28	.41	.33	.28	.40	.33	.27	.39	.32	.27	.38	.32	.27	.25
10.0	.38	.30	.25	.38	.30	.25	.37	.30	.25	.36	.29	.25	.35	.29	.25	.23



C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 4.950m [K=1.0000]
 Remarks:

WEC AND CCEC

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.309	.176	.056	.302	.172	.055	.289	.166	.053	.276	.159	.051	.265	.154	.050		
2.0	.295	.162	.050	.288	.159	.049	.277	.154	.048	.266	.149	.047	.256	.145	.046		
3.0	.274	.146	.044	.268	.144	.043	.258	.140	.042	.248	.136	.042	.239	.133	.041		
4.0	.253	.132	.039	.248	.130	.038	.239	.127	.038	.231	.124	.037	.223	.121	.037		
5.0	.234	.119	.035	.230	.118	.034	.222	.115	.034	.214	.113	.034	.207	.111	.033		
6.0	.217	.109	.031	.213	.108	.031	.206	.106	.031	.199	.103	.030	.193	.101	.030		
7.0	.202	.100	.028	.198	.099	.028	.192	.097	.028	.186	.095	.028	.180	.094	.027		
8.0	.188	.092	.026	.185	.091	.026	.180	.090	.026	.174	.088	.025	.169	.087	.025		
9.0	.176	.085	.024	.174	.085	.024	.168	.083	.024	.164	.082	.023	.159	.081	.023		
10.0	.166	.079	.022	.163	.079	.022	.159	.078	.022	.154	.077	.022	.150	.075	.022		

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.180	.156	.134	.154	.134	.116	.105	.092	.080	.061	.053	.047	.019	.017	.015	
2.0	.173	.132	.098	.148	.114	.084	.101	.079	.059	.058	.046	.035	.019	.015	.011	
3.0	.165	.114	.074	.142	.099	.064	.097	.069	.045	.056	.040	.026	.018	.013	.009	
4.0	.158	.101	.058	.135	.087	.050	.093	.061	.035	.054	.036	.021	.017	.012	.007	
5.0	.151	.091	.047	.129	.079	.041	.089	.055	.029	.052	.032	.017	.017	.011	.006	
6.0	.143	.082	.039	.123	.071	.034	.085	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.137	.076	.033	.117	.065	.029	.081	.046	.020	.047	.027	.012	.015	.009	.004	
8.0	.130	.070	.028	.112	.061	.025	.077	.042	.018	.045	.025	.010	.015	.008	.003	
9.0	.124	.065	.025	.107	.056	.022	.074	.040	.015	.043	.023	.009	.014	.008	.003	
10.0	.118	.061	.022	.102	.053	.019	.071	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 4.950m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	21.4	22.9	21.6	23.1	23.3	21.7	23.3	22.0	23.5	23.7
3H	22.7	24.1	23.0	24.4	24.6	23.3	24.7	23.6	25.0	25.2
4H	23.1	24.5	23.5	24.8	25.0	23.8	25.2	24.1	25.4	25.7
6H	23.3	24.6	23.6	24.9	25.1	24.1	25.4	24.5	25.7	26.0
8H	23.3	24.5	23.6	24.8	25.1	24.2	25.4	24.5	25.7	26.0
12H	23.2	24.4	23.6	24.7	25.0	24.1	25.3	24.5	25.6	25.9
4H 2H	22.0	23.4	22.3	23.6	23.9	22.3	23.7	22.6	23.9	24.2
3H	23.5	24.7	23.9	25.0	25.3	24.0	25.2	24.4	25.5	25.8
4H	24.1	25.1	24.4	25.5	25.8	24.7	25.8	25.1	26.1	26.4
6H	24.3	25.3	24.7	25.6	26.0	25.1	26.1	25.5	26.4	26.8
8H	24.3	25.2	24.7	25.6	26.0	25.2	26.1	25.6	26.4	26.8
12H	24.3	25.1	24.7	25.5	25.9	25.2	26.0	25.6	26.4	26.8
8H 4H	24.3	25.2	24.7	25.6	26.0	24.9	25.8	25.3	26.1	26.5
6H	24.6	25.4	25.1	25.8	26.2	25.4	26.1	25.8	26.5	26.9
8H	24.7	25.3	25.1	25.7	26.2	25.5	26.2	26.0	26.6	27.0
12H	24.6	25.2	25.1	25.6	26.1	25.5	26.1	26.0	26.5	27.0
12H 4H	24.3	25.1	24.7	25.5	25.9	24.9	25.7	25.3	26.1	26.5
6H	24.7	25.3	25.1	25.7	26.2	25.4	26.0	25.8	26.5	26.9
8H	24.7	25.3	25.2	25.7	26.2	25.5	26.1	26.0	26.5	27.0
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2				
1.5H	+ 0.2 / - 0.4					+ 0.2 / - 0.4				
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4				

CIE Pub.117 Corrected 319.1 lm Total Lamp Luminous Flux.(8log(F/F0) = -4.0)

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2015-11-10

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:4.950m [K=1.0000]
Remarks:


UTILIZATION FACTORS TABLE

REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	56	44	37	55	44	37	54	43	37	30
0.80	66	54	47	65	54	47	63	53	46	39
1.00	75	63	56	74	63	56	71	64	55	48
1.25	82	71	64	81	71	64	78	69	63	55
1.50	87	77	70	86	76	70	83	75	68	61
2.00	94	86	79	93	85	78	89	82	77	69
2.50	99	91	85	96	89	84	93	87	82	73
3.00	102	95	90	100	94	88	96	91	86	78
4.00	106	100	96	104	99	94	100	95	92	83
5.00	109	104	100	106	102	98	102	98	95	86
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 4.950m [K=1.0000]
 Remarks:


ISOCANDELA DIAGRAM



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:4.950m [K=1.0000]
Remarks:

AAI Figure




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:4.950m [K=1.0000]
Remarks:

ISOLUX DIAGRAM



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 4.950m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:12.00V I:0.9631A P:11.56W PF:1.0000 Lamp Flux:319.064x1 lm		
NAME: LED Strip	TYPE:Indoor lighting	WEIGHT:
SPEC.:5050RGB 60LED	DIM.: 1000*10*1MM	SERIAL No.:201511104
MFR.:	SUR.:1000*10mm	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	12421
L_0~180 (75) av	9915
L_0~180 (85) av	2188
L_90~270 (65) av	13559
L_90~270 (75) av	11547
L_90~270 (85) av	3685
L_45 (65) av	13013
L_45 (75) av	10649
L_45 (85) av	2079

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2015-11-10

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity:65.0%
Test Distance:4.950m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 5.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351
Humidity: 65.0%
Test Distance: 4.950m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90
0	101	101	101	101	101	101	100	101	100	101	100	100	100	100	100	100	100	100	100
5	100	100	99.9	99.9	99.7	99.4	99.4	99.4	99.3	99.4	99.3	99.4	99.2	99.2	99.2	99.2	99.2	99.3	99.3
10	98.7	98.5	98.3	98.2	98.1	97.8	97.7	97.8	97.7	97.8	97.7	97.8	97.6	97.7	97.7	97.8	97.7	97.9	97.9
15	96.5	96.3	96.0	96.0	95.8	95.6	95.5	95.6	95.6	95.7	95.7	95.8	95.6	95.7	95.8	95.9	95.9	96.0	96.0
20	93.7	93.5	93.3	93.2	93.0	92.8	92.8	93.0	92.9	93.1	93.1	93.3	93.2	93.3	93.4	93.6	93.6	93.8	93.9
25	90.3	90.1	89.8	89.8	89.7	89.5	89.5	89.7	89.8	90.0	90.1	90.4	90.2	90.3	90.4	90.6	90.6	90.9	90.9
30	86.2	86.0	85.8	85.8	85.7	85.6	85.6	85.9	86.0	86.3	86.4	86.7	86.6	86.7	86.8	87.0	87.0	87.3	87.3
35	81.4	81.4	81.1	81.2	81.0	81.1	81.1	81.5	81.6	81.9	82.0	82.4	82.4	82.4	82.5	82.7	82.7	83.1	83.1
40	76.1	76.0	75.8	75.9	75.8	75.9	76.1	76.4	76.6	77.0	77.1	77.5	77.5	77.6	77.6	77.9	77.9	78.2	78.3
45	70.2	70.2	70.0	70.1	70.0	70.2	70.4	70.8	71.0	71.5	71.5	71.9	72.0	72.2	72.1	72.4	72.4	72.8	72.9
50	63.3	63.3	63.0	63.3	63.2	63.5	63.7	64.3	64.6	65.1	65.2	65.7	65.7	66.0	65.9	66.2	66.2	66.5	66.5
55	55.4	55.4	55.2	55.4	55.5	55.8	56.1	56.7	57.1	57.7	57.9	58.4	58.4	58.8	58.6	58.9	58.9	59.2	59.1
60	46.6	46.6	46.5	46.7	46.8	47.2	47.5	48.1	48.5	49.2	49.4	49.9	50.0	50.3	50.3	50.5	50.5	50.7	50.6
65	36.8	37.0	36.8	37.2	37.2	37.7	37.9	38.6	39.0	39.7	39.9	40.5	40.5	40.8	40.8	41.1	41.0	41.3	41.2
70	26.6	26.7	26.7	27.0	27.1	27.5	27.8	28.5	28.9	29.6	29.7	30.3	30.3	30.6	30.6	30.9	30.8	31.1	30.9
75	16.3	16.5	16.5	16.9	17.0	17.4	17.7	18.3	18.6	19.3	19.4	19.9	19.8	20.1	20.1	20.4	20.3	20.5	20.3
80	6.68	6.99	6.95	7.38	7.43	7.93	8.12	8.71	8.94	9.55	9.58	10.0	9.95	10.2	10.1	10.4	10.2	10.4	10.1
85	0.01	0.00	0.01	0.00	0.01	0.18	0.32	0.72	0.89	1.34	1.33	1.69	1.58	1.76	1.63	1.78	1.64	1.76	1.52
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG

C Interval: 5.0DEG

Test Speed: HIGH

Temperature: 25.3DEG

Operators: DAMIN

Test Date: 2015-11-10

γ Range: 0 - 180DEG

γ Interval: 1.0DEG

Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351

Humidity: 65.0%

Test Distance: 4.950m [K=1.0000]

Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--2

UNIT: cd

C (DEG) γ (DEG)	95	100	105	110	115	120	125	130	135	140	145	150	155	160	165	170	175	180	185
0	100	100	100	100	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101
5	99.3	99.3	99.4	99.6	99.9	99.9	100.0	100	101	101	101	101	101	101	101	101	101	102	101
10	97.9	97.9	98.1	98.3	98.6	98.7	98.8	99.2	99.6	99.6	99.7	99.8	100	100	100	101	101	101	101
15	96.1	96.2	96.4	96.6	96.9	97.0	97.2	97.5	98.0	98.0	98.2	98.3	98.6	98.8	99.1	99.4	99.6	100	100
20	94.0	94.1	94.3	94.5	94.8	94.8	95.1	95.5	95.9	95.9	96.1	96.3	96.6	96.8	97.2	97.5	97.8	98.4	98.5
25	91.1	91.1	91.5	91.7	92.1	92.1	92.5	92.9	93.2	93.2	93.5	93.6	93.9	94.1	94.6	94.9	95.2	96.0	96.1
30	87.5	87.6	88.0	88.2	88.7	88.8	89.2	89.6	89.9	89.9	90.2	90.3	90.6	90.8	91.3	91.6	92.1	92.9	93.1
35	83.4	83.4	83.8	84.1	84.5	84.7	85.2	85.6	85.8	85.9	86.2	86.3	86.7	86.9	87.4	87.6	88.1	89.2	89.4
40	78.6	78.6	79.1	79.3	79.6	79.9	80.5	80.7	80.9	81.0	81.4	81.6	81.9	82.2	82.7	82.9	83.4	84.7	84.9
45	73.2	73.2	73.6	73.8	74.2	74.4	75.0	75.1	75.4	75.5	75.9	76.0	76.4	76.7	77.3	77.5	78.1	79.5	79.7
50	66.8	66.9	67.4	67.5	68.0	68.2	68.5	68.5	68.9	68.9	69.3	69.4	69.9	70.1	70.7	71.0	71.6	73.3	73.5
55	59.5	59.5	60.1	60.1	60.6	60.6	60.9	60.9	61.2	61.2	61.5	61.6	62.1	62.3	62.9	63.2	63.9	65.9	66.0
60	50.9	51.0	51.5	51.5	51.9	51.8	52.0	52.0	52.3	52.3	52.6	52.7	53.1	53.4	54.0	54.3	55.1	57.2	57.3
65	41.5	41.5	41.8	41.8	42.0	41.8	42.1	42.0	42.3	42.2	42.5	42.5	43.1	43.2	43.8	44.1	44.9	47.2	47.3
70	31.2	31.1	31.4	31.2	31.3	31.1	31.3	31.2	31.4	31.3	31.6	31.6	32.0	32.2	32.7	33.0	33.7	36.2	36.2
75	20.5	20.4	20.5	20.2	20.2	19.9	20.1	20.0	20.2	20.1	20.4	20.3	20.7	20.8	21.4	21.7	22.5	24.7	24.7
80	10.3	10.0	10.0	9.54	9.54	9.16	9.32	9.08	9.32	9.09	9.43	9.31	9.75	9.76	10.4	10.5	11.2	13.3	13.3
85	1.69	1.39	1.26	0.81	0.75	0.41	0.45	0.20	0.32	0.13	0.30	0.20	0.46	0.48	0.83	0.95	1.43	3.05	2.94
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 4.950m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--3

UNIT: cd

C (DEG) γ (DEG)	190	195	200	205	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280
0	101	101	101	101	100	101	100	101	100	100	100	100	100	100	100	100	100	100	100
5	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101
10	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101	100
15	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100.0	99.8	99.7
20	98.6	98.7	98.8	98.7	98.8	98.9	98.9	99.0	99.1	99.1	99.0	98.9	99.0	98.9	98.8	98.8	98.6	98.4	98.3
25	96.3	96.4	96.6	96.5	96.7	96.8	97.0	97.0	97.2	97.3	97.2	97.0	97.0	96.9	96.8	96.8	96.6	96.3	96.2
30	93.3	93.5	93.8	93.8	94.0	94.1	94.3	94.4	94.6	94.7	94.7	94.5	94.4	94.3	94.1	94.0	93.8	93.5	93.3
35	89.6	89.9	90.3	90.3	90.6	90.8	91.0	91.0	91.3	91.3	91.4	91.2	91.1	90.9	90.8	90.6	90.4	90.1	89.8
40	85.3	85.6	86.0	86.1	86.5	86.6	86.9	86.9	87.2	87.3	87.5	87.3	87.2	87.0	86.8	86.6	86.4	85.9	85.7
45	80.1	80.4	81.0	81.0	81.5	81.6	81.9	82.0	82.4	82.5	82.8	82.6	82.5	82.3	82.1	81.8	81.7	81.2	80.9
50	73.9	74.2	74.7	74.9	75.4	75.6	76.0	76.1	76.5	76.5	76.8	76.9	76.9	76.5	76.5	76.1	75.9	75.4	75.1
55	66.5	66.7	67.3	67.4	68.0	68.2	68.7	68.7	69.2	69.2	69.7	69.7	69.8	69.5	69.5	69.0	68.8	68.2	68.0
60	57.7	57.9	58.5	58.6	59.3	59.4	60.0	60.0	60.6	60.5	61.0	60.9	61.2	61.0	61.0	60.6	60.4	59.8	59.6
65	47.7	47.9	48.4	48.6	49.1	49.3	49.9	50.0	50.4	50.3	50.8	50.8	51.1	51.0	51.0	50.7	50.5	50.0	49.8
70	36.7	36.8	37.4	37.4	38.0	38.0	38.6	38.6	39.1	39.0	39.4	39.4	39.8	39.7	39.8	39.5	39.5	39.0	38.9
75	25.1	25.2	25.7	25.6	26.1	26.0	26.5	26.4	26.9	26.7	27.1	27.1	27.5	27.4	27.7	27.4	27.5	27.0	27.0
80	13.6	13.6	13.9	13.8	14.0	13.9	14.2	14.0	14.3	14.1	14.5	14.5	14.9	14.9	15.2	15.0	15.2	14.9	14.3
85	3.15	2.98	3.21	2.97	3.12	2.81	2.95	2.69	2.96	2.70	3.00	2.93	3.26	3.17	3.53	3.39	3.62	3.15	3.32
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: DAMIN
 Test Date: 2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-2000B_V1 SYSTEM V2.0.351
 Humidity: 65.0%
 Test Distance: 4.950m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Table--4

UNIT: cd

C (DEG) γ (DEG)	285	290	295	300	305	310	315	320	325	330	335	340	345	350	355				
0	100	100	101	101	101	101	101	101	101	101	101	101	101	101	101				
5	101	101	101	101	101	101	101	101	101	101	101	101	101	101	101				
10	100	100	101	100	100	100	100	100	99.9	99.8	99.6	99.5	99.4	99.4	99.1				
15	99.7	99.7	99.6	99.4	99.2	99.3	99.2	98.8	98.5	98.3	98.1	97.8	97.6	97.4	97.1				
20	98.1	98.1	98.1	97.7	97.5	97.5	97.4	96.9	96.5	96.2	95.8	95.5	95.2	94.9	94.5				
25	96.0	95.9	95.8	95.4	95.1	95.0	94.7	94.2	93.7	93.3	92.8	92.5	92.1	91.7	91.2				
30	93.1	93.0	92.8	92.3	92.0	91.9	91.4	90.9	90.3	89.8	89.2	88.8	88.2	87.8	87.2				
35	89.6	89.5	89.1	88.7	88.3	88.1	87.4	86.8	86.2	85.7	85.0	84.4	83.8	83.3	82.6				
40	85.4	85.3	84.8	84.3	83.8	83.5	82.7	82.2	81.4	80.9	79.6	79.2	78.5	78.2	77.5				
45	80.5	80.4	79.6	79.3	78.8	78.3	77.4	76.5	75.1	74.2	73.0	72.6	72.4	72.3	71.5				
50	74.7	74.4	73.7	73.4	72.7	71.9	70.0	69.0	68.1	67.3	66.5	66.1	65.8	65.7	64.9				
55	67.6	67.2	66.5	66.2	65.0	64.3	62.4	61.6	60.5	59.9	58.9	58.5	58.1	57.9	57.2				
60	59.0	58.8	58.0	56.8	55.3	55.5	53.8	53.0	51.9	51.3	50.3	49.8	49.3	49.1	48.3				
65	49.2	48.8	47.3	46.3	45.6	45.7	44.0	43.2	42.3	41.7	40.8	40.3	39.8	39.5	38.9				
70	38.2	36.9	36.3	35.5	35.1	34.7	33.3	32.8	31.9	31.4	30.5	30.0	29.4	29.2	28.6				
75	25.8	25.4	24.8	24.2	23.8	23.4	22.4	21.9	21.1	20.7	19.9	19.5	18.9	18.8	18.1				
80	14.2	14.0	13.2	12.9	12.6	12.3	11.5	11.1	10.4	10.1	9.55	9.30	8.83	8.76	8.25				
85	3.03	3.09	2.33	2.04	1.59	1.76	1.45	1.50	1.23	1.29	0.92	0.92	0.60	0.62	0.30				
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
95	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
115	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
120	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
125	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
130	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
135	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
140	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
145	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
150	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
155	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00				

C Range: 0 - 360DEG
 C Interval: 5.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2015-11-10

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-2000B_V1 SYSTEM V2.0.351
 Humidity:65.0%
 Test Distance:4.950m [K=1.0000]
 Remarks: