Fixture Type: Catalog Number: Project: Location: - 1011/16" H 91/16" + 14"+ ÷ :1%" + 13"+ Min:223/4" H 41/2' ÷ +15/16″ Max:1223/4" Min:121/4" 13%" Max:120¼" 1 ± 3%í″ 48" 48" ₽ R tŀ ill Р a F PD-81006 PD-81004 . ,... · Articulating arms • Universal Driver (120V-277V) concealed within the canopy • Six 12" and two 6" downrods included for PD-81006; Three 12" and one 6" downrods included for PD-81004 (additional downrods available) • Dimming: ELV (100% - 10%), 0-10V (100% - 5%), TRIAC (100% - 5%) • Rated Life: 50,000 hours

Color Temp: 3000K

• CRI: 90

ORDER NUMBER

Model	Height	Wattage	Voltage	LED Lumens	Delivered Lumens	Finish
PD-81004	3.63"	32W	120V-277V	2642	1669	AB Aged Brass
PD-81006	5.63"	45W		4135	2446	AN Aged Nickel

Example: PD-81004-AB

modernforms.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JAN 2020