© 2023 Kichler Lighting LLC. All Rights Reserved.

#### **MOTOR FINISH**



### **BLADE FINISHES**

Matte White





### **AR PERFORMANCE**

AIRFLOW Cubic Ft. Per Minute on High

6246

**RPM** Revolutions Per Minute on High

165

POWER USAGE Watts on High (Excludes Lights)

65

AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt

96

## **SPECIFICATIONS**

SPECIFICATIONS			
Performance			
CFM (High) Watts (High)	6246 65	RPM (High) Airflow Efficiency CFM/W (High)	165 96
Motor Specifications			
Amps (High) Motor Type	0.55 AC Induction	Motor Size Primary Material	172MM X 20MM Steel
Mounting/Installation			
Minimum Distance from Fan to Floor Lead Wire Length Low Ceiling Adaptable	7 feet 78" No	Interior/Exterior Location Rating Max Stem Tilt	Exterior Wet 30.00
Dimensions			
Downrod 1 Downrod 1 - Measurement B Base Backplate Blade Sweep Width	1.00 OD X 4.50" 11.50" 6.50" DIA 60 60.00"	Downrod 1 - Measurement A Downrod 1 - Measurement C Weight Height	14.00" 9.00" 17.59 LBS 14.00"
Light Source			
Downlight Option	Optional		
FIXTURE ATTRIBUTES			

Blade Finish & Specs			
Blade Finish 1 Blade Pitch Number of Blades	Matte White 13 4	Blade Material Blades Included	ABS Yes
Included Control			
Wall Control Included	No	Remote Included	No

Product/Ordering Information			
SKU UPC	300250MWH 783927559867	Finish Style	Matte White Transitional
Housing			
Fan Primary Control System	Pull Chain		

# Warranty

www.kichler.com/warranty

### **Compatible Accessories**

CoolTouch™ Handheld Control System Limited Function White, Universal Fan Remote Control White, Wall Control System Limited Function Multiple Finishes

### **ALSO IN THIS FAMILY**





300250SBK

300250SNB

You can see all products in this family by searching Kichler.com