## 60" Starkk Fan Matte White

© 2023 Kichler Lighting LLC. All Rights Reserved.

330180MWH

#### MOTOR FINISH



**BLADE FINISHES** 

Matte White



### **AR PERFORMANCE**

| 1 | AR PERFORMANCE   |   |   |         |  |
|---|--|---|---|---------|--|
|   | <b>AIRFLOW</b><br>Cubic Ft. Per Minute on High   | <b>RPM</b><br>Revolutions Per Minute on High          | POWER USAGE<br>Watts on High<br>(Excludes Lights)   |         | IRFLOW EFFICIENCY<br>Subic Ft. Per Minute Per Watt |
|   | 5316   | 113   | 76  |         | 70   |
| ; | SPECIFICATIONS   |   |   |         |  |
|   | Performance  |   |   |         |  |
|   | CFM (High)<br>Watts (High)   | 5316<br>76  | RPM (High)<br>Airflow Efficiency CFM/W (H   | -ligh)  | 113<br>70  |
|   | Motor Specifications   |   |   |         |  |
|   | Amps (High)<br>Motor Type  | 0.60<br>AC Induction                                  | Motor Size<br>Primary Material  |         | 188MM X 25MM<br>Steel                              |
|   | Mounting/Installation  |   |   |         |  |
|   | Minimum Distance from Fan to Floor<br>Lead Wire Length<br>Low Ceiling Adaptable                        | 7 feet<br>78"<br>No                                   | Interior/Exterior<br>Location Rating<br>Max Stem Tilt   |         | Interior<br>CSA UL Listed Dry<br>18.00             |
|   | Dimensions   |   |   |         |  |
|   | Downrod 1<br>Downrod 1 - Measurement B<br>Base Backplate<br>Blade Sweep<br>Width                       | 1.00 OD X 4.50"<br>9.75"<br>6.25" DIA<br>60<br>60.00" | Downrod 1 - Measurement<br>Downrod 1 - Measurement<br>Weight<br>Height  |         | 14.25"<br>10.50"<br>21.41 LBS<br>14.25"            |
|   | Light Source   |   |   |         |  |
|   | Downlight Included<br>Color Rendering Index<br>Initial Lumens<br>Diffuser Description<br>Lamp Included | Yes<br>80<br>1600<br>Etched Cased Opal<br>Integrated  | Downlight Option<br>Kelvin Temperature<br>Lumens/watt (efficacy)<br>Downward-facing Bulbs<br># of Bulbs/LED Modules |         | Integrated<br>3000K<br>94.00<br>X 17W<br>1         |
|   | Photometrics   |   |   |         |  |
|   | Color Temperature Range  | 3000  | Delivered Efficacy (Lumens  | s/Watt) | 94   |
|   |  |   |   |         |  |

### **FIXTURE ATTRIBUTES**

# **KICHLER**

| Blade Finish & Specs                               |                           |   |                             |
|--|---------------------------|---|-----------------------------|
| Blade Finish 1<br>Blade Pitch<br>Blades Reversible | Matte White<br>14<br>Yes  | Blade Material<br>Blades Included<br>Number of Blades | Wood<br>Yes<br>5            |
| Included Control                                   |                           |   |                             |
| Wall Control Included                              | No                        | Remote Included                                       | No                          |
| Product/Ordering Information                       |                           |   |                             |
| SKU<br>UPC   | 330180MWH<br>783927471251 | Finish<br>Style                                       | Matte White<br>Transitional |
| Housing  |                           |   |                             |
| Fan Primary Control System                         | Pull Chain                |   |                             |
| Warranty   |                           |   |                             |
| www.kichler.com/warranty                           |                           |   |                             |

### Compatible Accessories

CoolTouch™ Handheld Control System Limited Function White, Universal Fan Remote Control White, Wall Control System Limited Function Multiple Finishes

#### ALSO IN THIS FAMILY



You can see all products in this family by searching Kichler.com

# **KICHLER**