

PRODUCT DETAILS:

- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Wiring and surface mount kit are supplied
- Equipped with a 120/277 universal driver. 0-10 dimming.
- LED integrated components carry a 10-year limited warranty
- Bold lines and a clean, minimalist style complement contemporary architecture

TAPER

15288BZ

TAPER LED BOLLARD

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
	YES - CL TYPE DIMMER (SSL7A)

DIMENSIONS	
WIDTH:	6"
HEIGHT:	36"
DEPTH:	6
WEIGHT:	16.5lb

LIGHT SOURCE	
LIGHT SOURCE:	Integrated LED
LED NAME:	(4) GL-3030
WATTAGE:	28w LED *Included
VOLTAGE:	120v/277v
COLOR TEMP:	3000
LUMENS:	2800
CRI:	80
INCANDESCENT EQUIVALENCY:	4 x 60w
DIMMABLE:	YES - CL TYPE DIMMER (SSL7A)

MOUNTING	
LEAD WIRE:	1 X 6"

	_
SHIPPING	
CARTON LENGTH:	10
CARTON WIDTH:	10
CARTON HEIGHT:	41
CARTON WEIGHT:	18.6

