



## Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)

- A wiring kit and ground spike are supplied
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC.
  Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association
  Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- LumaCore Series products carry a lifetime limited warranty

## LUMACORE ACCENT SPOT LIGHT

## 15300BZ-LMA30K

VARIABLE OUTPUT LED 12W 3000K FLOOD SPOT 12V

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Frosted Lens
DIMMABLE:	No

DIMENSIONS	
WIDTH:	4.5"
HEIGHT:	4"
DEPTH:	4.5
WEIGHT:	1lb

LIGHT SOURCE	
LIGHT SOURCE:	LumaCore
LED NAME:	30G4SE-12W
WATTAGE:	12w, 8w, 5w,3w LumaCore LED *Included
VOLTAGE:	12v
COLOR TEMP:	3000
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	No

MOUNTING	
LEAD WIRE:	1 X 18"

SHIPPING	
CARTON LENGTH:	8.7
CARTON WIDTH:	18.9
CARTON HEIGHT:	17.7
CARTON WEIGHT:	2



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539