



Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)

- A wiring kit and ground spike are supplied
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC.
 Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association
 Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- LumaCore Series products carry a lifetime limited warranty

LUMACORE ACCENT SPOT LIGHT

15300SK-LMA30K

VARIABLE OUTPUT LED 12W 3000K FLOOD SPOT 12V

| DETAILS | |
|-----------|--------------|
| FINISH: | Satin Black |
| MATERIAL: | Aluminum |
| GLASS: | Frosted Lens |
| DIMMABLE: | No |

| DIMENSIONS | |
|------------|------|
| WIDTH: | 4.5" |
| HEIGHT: | 4" |
| DEPTH: | 4.5 |
| WEIGHT: | 1lb |

| LIGHT SOURCE | |
|------------------------------|---|
| LIGHT SOURCE: | LumaCore |
| LED NAME: | 30G4SE-12W |
| WATTAGE: | 12w, 8w, 5w, 3w LumaCore LED *Included |
| VOLTAGE: | 12v |
| COLOR TEMP: | 3000 |
| CRI: | 80 |
| INCANDESCENT EQUIVALENCY: | 1 x 60w, 45w, 35w, 25w |
| DIMMABLE: | No |

| MOUNTING | |
|------------|---------|
| LEAD WIRE: | 1 X 18" |

| SHIPPING |] |
|----------------|------|
| CARTON LENGTH: | 8.7 |
| CARTON WIDTH: | 18.9 |
| CARTON HEIGHT: | 17.7 |
| CARTON WEIGHT: | 2 |



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539