

LUMACORE ACCENT SPOT LIGHT

1536BZ-LMA30K

VARIABLE OUTPUT LED 3K SPOT

The Variable Output LumaCORE LED accent lighting system is an expertly engineered core that withstands the elements and provides the user with full control over wattage and beam spread, all in innovative single design.

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Clear Lens
DIMMABLE:	No

DIMENSIONS	
WIDTH:	5.8"
HEIGHT:	3.3"
DEPTH:	2.5
WEIGHT:	1lb

LIGHT SOURCE	
LIGHT SOURCE:	LumaCore
LED NAME:	30G4SE-12W
WATTAGE:	12w, 8w, 5w, 3w LumaCore LED *Included
VOLTAGE:	12v
COLOR TEMP:	3000
LUMENS:	750
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	No
TRANSFORMER REQUIRED:	Yes

MOUNTING	
LEAD WIRE:	1 X 18"

SHIPPING	
CARTON LENGTH:	11.5
CARTON WIDTH:	4.9
CARTON HEIGHT:	2.8
CARTON WEIGHT:	1.1



PRODUCT DETAILS:

- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20° Spot, 40° Flood, 60° Flood
- A wiring kit and ground spike are supplied
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Optional performance lenses available
- LumaCore Series products carry a lifetime limited warranty