

PRODUCT DETA





- A wiring kit and ground spike are supplied
 Suitable for use in wet (outdoor direct rain or sprint er) locations as defined by NEC and CEC.
 Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association
- Product Safety Standards
 Photometrics are based off bulb photometrics.
 Our Estate Collections boast a breadth of fixtures defined by coordinating composition, enduring architecture, and time-honored craftsmanship, designed to meet the needs of expansive properties with extended outdoor living spaces. From the entrance of your driveway to the depths of your backyard, these collections provide cohesive design for stately exteriors.
- · 5-year finish warranty
- · LED Bulbs carry a 3-year limited warranty
- · The Coastal Elements Collection offers versatile designs, constructed of composite materials and coated with anti-fading finishes, for maximum durability in harsh climates
- · Sophisticated and streamlined design, durable construction and a timeless finish complement any architectural style

REPUBLIC

15558BK-LL

REPUBLIC LED PATH LIGHT

Republic's striking double frame design, constructed from a composite material and treated with an antifading agent for maximum durability, is at home on the coast or a country lodge. The Oil Rubbed Bronze, Satin Nickel and Black resilience finishes feature a 5-year warranty and are resistant to rust and corrosion. Vintage filament bulbs are recommended to complete a stylish look.

DETAILS	
FINISH:	Black
MATERIAL:	Composite
GLASS:	Etched
DIMMABLE:	YES - MLV ON TRANSFORMER PRIMARY

DIMENSIONS	
WIDTH:	6"
HEIGHT:	24"
DEPTH:	5.8
WEIGHT:	2lb

	1
LIGHT SOURCE	
LIGHT SOURCE:	Socketed
LED NAME:	00T5-27LED-1.5
WATTAGE:	1-1.50w T5 LED *Included
VOLTAGE:	12v
COLOR TEMP:	2700
CRI:	90
INCANDESCENT EQUIVALENCY:	1 x 25w
DIMMABLE:	YES - MLV ON TRANSFORMER PRIMARY
TRANSFORMER REQUIRED:	Yes

MOUNTING	
LEAD WIRE:	1 X 36"

SHIPPING	
CARTON LENGTH:	26
CARTON WIDTH:	7.5
CARTON HEIGHT:	7.5
CARTON WEIGHT:	4.5



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539