

# WELL LIGHT

## 55702MZ-LMA27K

VARIABLE OUTPUT LED 2700K WELL LIGHT  
120V



| DETAILS   |              |
|-----------|--------------|
| FINISH:   | Matte Bronze |
| MATERIAL: | Aluminum     |
| GLASS:    | Clear Lens   |
| DIMMABLE: | NO           |

| DIMENSIONS |      |
|------------|------|
| WIDTH:     | 4.5" |
| HEIGHT:    | 4"   |
| DEPTH:     | 4.5  |
| WEIGHT:    | 3lb  |

| LIGHT SOURCE              |  |
|---------------------------|--|
| LIGHT SOURCE:             | LumaCore                               |
| LED NAME:                 | 27G4SE-120V                            |
| WATTAGE:                  | 12w, 8w, 5w, 3w LumaCore LED *Included |
| VOLTAGE:                  | 120v                                   |
| COLOR TEMP:               | 2700                                   |
| CRI:                      | 80                                     |
| INCANDESCENT EQUIVALENCY: | 1 x 60w, 45w, 35w, 25w                 |
| DIMMABLE:                 | NO                                     |

| MOUNTING   |         |
|------------|---------|
| LEAD WIRE: | 1 X 96" |

| SHIPPING       |      |
|----------------|------|
| CARTON LENGTH: | 23.5 |
| CARTON WIDTH:  | 7.5  |
| CARTON HEIGHT: | 5    |
| CARTON WEIGHT: | 2.5  |

### PRODUCT DETAILS:

- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Three lens options offer versatility in beam spread via an easy to remove and insert assemble - includes: 20° Spot, 40° Flood, 60° Flood
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- Optimal drive-over protection up to 4,500 lbs
- PVC constructed concrete pour kit and burial sleeve are supplied
- Optional performance lenses available

# HINKLEY

HINKLEY  
33000 Pin Oak Parkway  
Avon Lake, OH 44012

PHONE: (440) 653-5500  
Toll Free: 1 (800) 446-5539

[hinkley.com](http://hinkley.com)