

Cabot

Pendant 4CCT

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Civita usa Tura au

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-53448 48"	2700K 3000K 3500K 4000K	BK Black	40 W 40 W 40 W 40 W	2560 2560 2560 2560	901 901 901 901

Example: PD-53448-40-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

In the round. Rings of light glow softly through flush opal diffusers. Perfectly tethered to each other, this foldable design can be adjusted as desired along its linear length.

FEATURES

- Contracts and extends for an adjustable length and customized look
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Spin-on round canopy with minimal hardware
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 3500K,2700K,4000K,3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed

Construction: Extruded Aluminum body with silicon diffuser



FINISHES:



LINE DRAWING:

