

Corkscrew

Pendant 4CCT

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-39443 43"	2700K 3000K 3500K 4000K	BK Black	38 W 38 W 38 W 38 W	2862 2862 2862 2862	1785 1785 1785 1785 1785

Example: **PD-39443-40-BK**

For custom requests please contact customs@waclighting.com

DESCRIPTION

A playful band of light spirals around a linear bar. This looped structure delivers artful style along with a soft layer of multi-directional illumination.

- Low profile, adjustable powered aircraft cables for an ultra-clean look
- · May be mounted on slope ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Rectangular canopy with minimal hardware
- Driver concealed within the canopy

SPECIFICATIONS

4000K,2700K,3000K,3500K Color Temp:

120-277V,50/60Hz Input:

90 CRI:

ELV: 100-10% ,TRIAC: 100-5% Dimming:

50000 Hours Rated Life: ETL, cETL Standards:

Damp Location Listed

Aluminum body, silicone diffuser Construction:



FINISHES:



LINE DRAWING:

