WAC LIGHTING

Ferrous

Pendant 4CCT

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-33436 36"	2700K 3000K 3500K 4000K	BK Black	40 W 40 W 40 W 40 W	2300 2300 2300 2300	1615 1615 1615 1615

Example: PD-33436-40-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Free-wheeling. Strong angles converge, forming a bespoke ring of ambient light.

FEATURES

- Adjustable arms for a customized look
- Three 12" and one 6" downrods included (additional downrods available)
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Spin-on round canopy with minimal hardware
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp:	4000K,3500K,3000K,2700K		
Input:	120-277V,50/60Hz		
CRI:	90		
Dimming:	ELV: 100-10% , 0-10V: 100-5%,TRIAC: 100-5%		
Rated Life:	50000 Hours		
Standards:	ETL, cETL		
	Damp Location Listed		
Construction:	Extruded Aluminum body with acrylic diffuser		

Fixture Type:

Catalog Number:

Project:

Location:




FINISHES:



Black

LINE DRAWING:



waclighting.com | Phone (800) 526.2588 | Fax (800) 526.2585 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. April 2024