

WAC LIGHTING

Edgeless

Ceiling and Wall Mount

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

| Model & Size | Color Temp & CRI | Watt | Lumens | Finish |
|--------------|------------------------------------|------|--------|----------|
| FM-240505 | 9CS | 15W | 1330 | BK Black |
| FM-240508 | 2700K/3000K/3500K/4000K/5000K - 90 | 20W | 1985 | WT White |
| FM-240512 | 9CS | 30W | 2750 | |
| | 2700K/3000K/3500K/4000K/5000K - 90 | | | |
| | 9CS | | | |
| | 2700K/3000K/3500K/4000K/5000K - 90 | | | |

Example: **FM-240505-9CS-BK**

DESCRIPTION

Edgeless LED luminaires are designed with a low profile and slim trim. They are engineered for smooth, glare-free, consistent illumination. A welcome addition to ceilings and walls for various applications.

FEATURES


- Multiple LED array for uniform illumination
- Designed with slim trim to maximize light emitting surface
- 5-CCT Switchable between 2700K and 5000K
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

| | |
|-----------------|--|
| Construction: | Aluminum with white acrylic diffuser |
| Power: | 15W, 20W, 30W |
| Input: | 120 VAC, 50/60Hz |
| Dimming: | ELV: 100-5% , TRIAC: 100-5% |
| Light Source: | Integrated LED |
| Lens: | Acrylic Diffuser |
| Rated Life: | 50000 Hours |
| Mounting: | Installs over a 3", 4" or 3/0-4/0 hybrid junction box, Can be mounted on ceiling or wall in all orientations |
| Finish: | Electrostatically Powder Coated: White, Black |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, ADA |



FINISHES:



LINE DRAWING:

