

Gaze

Pendant 4CCT

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-23412 12"	2700K 3000K 3500K 4000K	BK Black BN Brushed Nickel	12 W 12 W 12 W 12 W	570 570 570 570	485 485 485 485

Example: **PD-23412-40-BN**

For custom requests please contact customs@waclighting.com

DESCRIPTION

Half and half. A sphere composed of equal parts clear and frosted glass brings your home to life with a combination of bright and diffuse illumination.

FEATURES

- Three 12" and one 6" downrods included (additional downrods available)
- · May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Spin-on round canopy with minimal hardware
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 3000K,4000K,2700K,3500K

Input: 120/277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed

Construction: Aluminum hardware with glass diffuser



Civita usa Tura au

FINISHES:



Brushed B Nickel

LINE DRAWING:

REPLACEMENT PARTS

RPL-GLA-23412 - RPL Glass for PD-23412 RPL-ROD-IN12-BK-01 - 12" Rod BK RPL-ROD-IN12-BN2-1 - 12" Rod BN RPL-ROD-IN06-BK-01 - 6" Rod BK RPL-ROD-IN06-BN2-1 - 6" Rod BN

