


HR-3LED-R15A

3.5" Aether Remodel Housing

IC-Rated – Airtight

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

IC-Rated, Airtight,
For use with R3ARDT, R3ASDT 3.5" Aether series trims.

FEATURES

- Airtight
- Cutout: 4 5/8"
- 120 - 277 VAC Input
- Provided with push-in wire connector for easy installation
- Accommodates ceiling thickness from 1/2"-1"
- 5 year WAC Lighting product warranty
- Does not accommodate adjustments

ORDER NUMBER

HR-3LED-R15A

*Remodel
IC-Rated, Airtight*

SPECIFICATIONS

Construction: Aluminum housing and junction box are 20 gauge steel.

J-Box: Three knockouts for ease of installation. Rated for branch wiring.

Driver: Electronic driver, 120 - 277VAC input, 15W output.
Power factor >0.9. Dimming with thermal protection.

Mounting: Three heavy gauge inner retention clips push out onto ceiling or other mounting surface to firmly hold housing in place.
Accommodates surfaces from 1/2"-1" thick. 4 5/8" cutout hole.

Dimming: 0-10V Dimming: 100%-0%
ELV Dimming: 100%-5% (120V only)

Standards: Airtight
ETL & cETL Listed.

COMPATIBLE TRIMS See trim spec sheets for complete order number and specifications.

Aether 3.5"

R3ARDT Series
Round, IC-Rated

R3ASDT Series
Square, IC-Rated

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760