

Ice Cube

Square Multi Light 4CCT

Model & Size	Color Temp & CRI		Watt	Lumens	Finish
PD-29313S 8" - 13 Lights	2 700K/3000K/3500K/4000K	90	93 W	4970	AB Aged Brass BK Black

Example: PD-29313S-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- \bullet NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 13, 25, & 41 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distrubuted evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K

Input: 120-277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed

Construction: Steel frame with K9 crystal diffuser



Fixture Type:

Project:

Location:

Catalog Number:

FINISHES:






Black

Aged Brass

LINE DRAWING:

REPLACEMENT PARTS

RPL-GLA-29308 - PD-29308 Crystal



WAC LIGHTING

Ice Cube

Square Multi Light 4CCT

Model & Size		Color Temp & CRI		Watt	Lumens	Finish	
PD-29325S 25 Lights	8" -	2 700K/3000K/3500K/4000K	90	180 W	9640		Aged Brass Black

Example: PD-29325S-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- \bullet NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 13, 25, & 41 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distrubuted evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K

Input: 120-277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed

Construction: Steel frame with K9 crystal diffuser



Fixture Type:

Project:

Location:

Catalog Number:

FINISHES:






Black Aged Brass

LINE DRAWING:

REPLACEMENT PARTS

RPL-GLA-29308 - PD-29308 Crystal



PD-29325S

WAC LIGHTING

Ice Cube

Square Multi Light 4CCT

Model & Size		Color Temp & CRI		Watt	Lumens	Finish	
PD-29341S 41 Lights	8" -	2 700K/3000K/3500K/4000K	90	294 W	15870		Aged Brass Black

Example: PD-29341S-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Faceted like a hand-cut jewel, adding a dash of chic to a room's ensemble.

FEATURES

- K9 crystal
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- \bullet NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs.
- This fixture in the 13, 25, & 41 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distrubuted evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K

Input: 120-277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10%, 0-10V: 100-5%, TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed

Construction: Steel frame with K9 crystal diffuser

Fixture Type:

Project:

Location:

Catalog Number:

FINISHES:



Black



Aged Brass

LINE DRAWING:

REPLACEMENT PARTS

RPL-GLA-29308 - PD-29308 Crystal

