

Quill

Round Multi Light 4CCT

| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |
| Project: | |
| Location: | |

| Model & Size | Color Temp & CRI | | Watt | Lumens | Finish | |
|-----------------------------|-----------------------------|----|------|--------|--------|-------------------------------|
| PD-59403R 16" - 3 Lights | 2 700K/3000K/3500K/4000K | 90 | 24 W | 1558 | BK | Aged Brass Black Chrome |

Example: PD-59403R-CH

For custom requests please contact customs@waclighting.com

DESCRIPTION

Precisely lined. V-groove flared glass radiates a prismatic glow. Staggered elements create a sense of motion, heightening the drama of this statement piece.

FEATURES

- V cut glass diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K

Input: 120/277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed


Construction: Aluminum Hardware with Glass body



FINISHES:



LINE DRAWING:



PD-59403R



Quill

Round Multi Light 4CCT

| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |
| Project: | |
| Location: | |
| | |

| Model & Size | | Color Temp & CRI | | Watt | Lumens | Finish | |
|--------------|-------|------------------------|----|------|--------|--------|------------|
| PD-59405R | 16" - | | | 40 W | 2597 | AB | Aged Brass |
| 5 Lights | | | | | | BK | Black |
| | | 2 | | | | CH | Chrome |
| | | 700K/3000K/3500K/4000K | 90 | | | | |
| | | | | | | | |

Example: PD-59405R-CH

For custom requests please contact customs@waclighting.com

DESCRIPTION

Precisely lined. V-groove flared glass radiates a prismatic glow. Staggered elements create a sense of motion, heightening the drama of this statement piece.

FEATURES

- V cut glass diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K

Input: 120/277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed


Construction: Aluminum Hardware with Glass body



FINISHES:



LINE DRAWING:



PD-59405R

WAC LIGHTING

Quill

Round Multi Light 4CCT

| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |
| Project: | |
| Location: | |

| Model & Size | Color Temp & CRI | | Watt | Lumens | Finish |
|-------------------------|-----------------------------|----|------|--------|---------------------------|
| PD-59409R 1 9 Lights | 6" - | | 72 W | 4674 | AB Aged Brass BK Black |
| | 2 700K/3000K/3500K/4000K | 90 | | | CH Chrome |

Example: PD-59409R-CH

For custom requests please contact customs@waclighting.com

DESCRIPTION

Precisely lined. V-groove flared glass radiates a prismatic glow. Staggered elements create a sense of motion, heightening the drama of this statement piece.

FEATURES

- V cut glass diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K

Input: 120/277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed

Construction: Aluminum Hardware with Glass body



FINISHES:








Aged Brass Black

Chrome

LINE DRAWING:



WAC LIGHTING

Quill

Round Multi Light 4CCT

| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |
| Project: | |
| Location: | |
| | |

| Model & Size Color Temp & CRI Watt Lumens | Finish |
|--|--|
| PD-59415R 16" - 15 Lights 2 700K/3000K/3500K/4000K 90 7790 | AB Aged Brass BK Black CH Chrome |

Example: PD-59415R-CH

For custom requests please contact customs@waclighting.com

DESCRIPTION

Precisely lined. V-groove flared glass radiates a prismatic glow. Staggered elements create a sense of motion, heightening the drama of this statement piece.

FEATURES

- · V cut glass diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K

Input: 120/277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed


Construction: Aluminum Hardware with Glass body



FINISHES:



LINE DRAWING:



WAC LIGHTING

Quill

Round Multi Light 4CCT

| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |
| Project: | |
| Location: | |

| Model & Size | Color Temp & CRI | | Watt | Lumens | Finish | |
|------------------------------|-----------------------------|----|-------|--------|--------------------------|--|
| PD-59421R 16" - 21 Lights | 2 700K/3000K/3500K/4000K | 90 | 168 W | 10905 | AB Ag BK Bla CH Ch | |

Example: PD-59421R-CH

For custom requests please contact customs@waclighting.com

DESCRIPTION

Precisely lined. V-groove flared glass radiates a prismatic glow. Staggered elements create a sense of motion, heightening the drama of this statement piece.

FEATURES

- · V cut glass diffuser
- Low profile, adjustable powered aircraft cables for an ultra-clean look
- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- NEC CODE (314.24) requires that ceiling outlet boxes in the U.S. support up to 50 lbs
- This fixture in the 21 light format exceeds 50 lbs. and must be installed adequately on the ceiling with weight distrubuted evenly on the mounting backplate.
- Driver concealed within the canopy

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K

Input: 120/277V,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 50000 Hours
Standards: ETL, cETL

Damp Location Listed


Construction: Aluminum Hardware with Glass body



FINISHES:



LINE DRAWING:



PD-59421R