


AETHER ATOMIC

R1ARAT - Round Adjustable Trim

WAC



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Minuscule and mighty, peerless and powerful, the new potent Aether Atomic launches into the light. An engineering recessed marvel for next generation futurists. Sublime and serviceable, it's an icon for the ages. Atomic breaks the mold with robust illumination from a diminutive aperture, for a clean, quiet ceiling.

FEATURES

- Robust lumen output from a small aperture
- 0 - 20° vertical tilt and 365° horizontal rotation (requires R1A-TOOL, sold separately)
- Field changeable beam angle with reflectors provided
- Low profile housing for installation in shallow plenums
- 5 year warranty

SPECIFICATIONS

- Construction:** Injection molded polycarbonate low glare trim
- Dimming:** 100% - 1% ELV, TRIAC and 0-10V
- Input Power:** 11W
- Light Source:** High output COB LED rated life of 50,000 hours
- Finish:** Black, Black/White, Gold/White, Haze/White, White
- Standards:** ETL & cETL Damp location listed, IC rated Airtight Title 24 JA8 Compliant

Trims (Order Housing and Power Supply Separately)	Model	Beam	Color Temp	CRI	Lumens	CBCP	Finishes
	<p>R1ARAT Round Adjustable Trim (F beam reflector pre-installed in housing, N and W beam reflectors included)</p>	N 26°	2700K	90	890	2860	BK Black BKWT Black/White GLWT Gold/White HZWT Haze/White WT White
			3000K		955	3075	
			3500K		1020	3290	
			4000K		1090	3505	
		F 36°	2700K	90	875	2320	
			3000K		940	2490	
			3500K		1005	2665	
			4000K		1075	2840	
		W 55°	2700K	90	745	755	
			3000K		800	815	
			3500K		855	870	
			4000K		910	925	

R1A ____ - ____

Example: **R1ARAT-BKWT**

Please see next page for housing, power supply and tool units (required)

AETHER ATOMIC

R1ARAT - Round Adjustable Trim



Housing (Required) - Order separately from trims

	Model	Power	Color Temp	CRI
	R1ARANT Round Trim IC-Rated, Airtight	11W	927 2700K	90
			930 3000K	
			935 3500K	
			940 4000K	

R1ARANT-__

Example: **R1ARANT-927**

Remote Power Supply (Required) - Order separately from trims and housings

	Model	Input	Output	Dimmable	
	PS-0600A-UR1	120V - 277V	1 Channel UL Class 2	100%-1% ELV, TRIAC, 0-10V	8 3/4" x 2" x 1 3/8"
	PS-0600A-UR6	120V - 277V	6 Channels UL Class 2	100%-1% ELV, TRIAC, 0-10V	10 7/8" x 3 7/8" x 1 3/8"

Example: **PS-0600A-UR6**

Home-run wiring. Recommended maximum distance between power supply and compatible light fixture is shown in below table:

	18 AWG	16 AWG	14 AWG	12 AWG
Maximum distance between power supply and light fixture	100 ft	150 ft	200 ft	250 ft

Accessory (Sold Separately)

	Model	Description
	R1A-TOOL	Tool for angle adjustment and removal of trim and light engine

Example: **R1A-TOOL**

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761