

## Stag

## **Outdoor Wall Sconce**

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W29118 18"	3000K	AL Brushed Aluminum	16W	1265	789
	3500K	BK Black	16W	1424	883
	4000K	WT White	16W	1299	807

Example: WS-W29118-40-WT

For custom requests please contact customs@waclighting.com

## DESCRIPTION

Majestic, keen and sharp. A signature silhouette.

## **FEATURES**

- Back lit with indirect illumination
- 3CCT (3000K/3500K/4000K) selectable switch
- Option to pre-select color temperature or adjust in the field
- · ACLED driverless technology
- 5 year warranty

#### **SPECIFICATIONS**

 Color Temp:
 3000K,3500K,4000K

 Input:
 120 VAC,50/60Hz

CRI: 90

**Dimming:** ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations


Standards: ETL, cETL,IP65,Title 24 JA8 Compliant

Wet Location Listed


Construction: Aluminum body, frosted glass diffuser



### **FINISHES:**



## **LINE DRAWING:**



WS-W29118



# Stag

## **Outdoor Wall Sconce**

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W29124 24"	3000K 3500K 4000K	AL Brushed Aluminum BK Black	24 W 24 W 24 W	1650 1650 1650	1100 1100 1100

Example: WS-W29124-40-BK

For custom requests please contact customs@waclighting.com

## DESCRIPTION

Majestic, keen and sharp. A signature silhouette.

#### **FEATURES**

- · Back lit with indirect illumination
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K.
- 0-10V dimming option (LDS065M010AFE-LO1) available (special order), unit dimensions: 3.4"  $\times$  1.2"  $\times$  0.5"
- · ACLED driverless technology

#### **SPECIFICATIONS**

 Color Temp:
 4000K,3500K,3000K

 Input:
 120 VAC,50/60Hz

CRI: 90

**Dimming:** ELV: 100-10% ,TRIAC: 100-5%

Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL, Title 24 JA8 Compliant

Wet Location Listed


Construction: Aluminum body, frosted glass diffuser

## REPLACEMENT PARTS


RPL-GLA-29124 - Glass



### **FINISHES:**



## LINE DRAWING:



WS-W29124