WAC LIGHTING

Tusk

Mini Pendant 4CCT

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
PD-29425 25"	2700K 3000K 3500K 4000K	BK Black BN Brushed Nickel	15 W 15 W 15 W 15 W	1350 1350 1350 1350	720 720 720 720

Example: PD-29425-40-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

Deconstructed. Offset curves lined with soft LED illumination are mounted on a round backplate, creating a strong visual presence in modern rooms.

FEATURES

- Three 12" and one 6" downrods included (additional downrods available)
- May be mounted on a sloped ceiling
- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- · Option to pre-select color temperature or adjust in the field
- Spin-on round canopy with minimal hardware
- Driver concealed within the canopy


SPECIFICATIONS

Color Temp:	3000K,2700K,3500K,4000K		
Input:	120/277V,50/60Hz		
CRI:	90		
Dimming:	ELV: 100-10% ,TRIAC: 100-5%		
Rated Life:	50000 Hours		
Standards:	ETL, cETL		
	Damp Location Listed		
Construction:	Aluminum body with silicone diffuser		

FINISHES:



LINE DRAWING:



waclighting.com | Phone (800) 526.2588 | Fax (800) 526.2585 | Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. April 2024

PD-29425

Fixture Type:

Catalog Number:

Project:

Location:



