# PANDORA
WS25336

WALL

DESCRIPTION

Dual square profile linear aluminum arms with rectangular wall mount. Inset opal polymeric diffusers. Finely textured plate or powder-coated finish. Wall emitting lights with rotational adjustment.

WS25336-BG	WS25336-BK	WS25336-BN	WS25336-WH
Brushed Gold	Black	Brushed Nickel	White

SPECIFICATION DETAILS

Fixture Dimensions	W36" x H4-5/8" x E3-7/8"
Light Source	LED with DC Driver
Wattage	26W
Total Lumens	2290lm
Delivered Lumens	BK-650lm*; BN-1150lm*; WH-1330lm*;
Voltage	120V
Color Temperature	3000K
CRI (Ra)	90CRI
Optional Color Temps	2700K - 5000K Available, Minimum Order Quantities Apply
LED Rated Life	50,000 hours
Dimming	100% - 10%, TRIAC or ELV Dimmer (Not Included)
Diffuser Details	White Acrylic Diffuser
ADA Compliant	Yes
Location	Dry
Illumination Direction	Fontlight Illumination
Mounting Style	All Orientation; Wall;
CEC Title 24 JA8	Yes, JA8-2022
Canopy Dimensions	W5-3/8" x H4-5/8" x E3/8"
Paint Finish	BG01; BK02; BN02; WH02;

* For custom options, consult factory for details.

* For warranty information, please visit www.kuzcolighting.com/warranty

Finish
BK - Black
BN - Brushed Nickel
BG - Brushed Gold
WH - White

Backplate Accessory (optional)

5-3/8"
5-1/8"
5/8"
3"
4-5/8"
1-5/8"
3/8"
3-7/8"
36"

KUZCO

COMMENT

ETL LISTED
c   us
Intertek