


Architectural Linear Strip

20W | Colour Selectable | 120-347V | 2ft

Elevate your space by creating your own custom lighting design Ideal for use in offices, conference rooms, hallways, educational facilities, and more











TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	2,300 lm
Efficacy	115 lm/W
CCT	Selectable (30K/35K/40K)
CRI	≥80
Dimmable	0-10V
L70 Life	>50,000 hrs
Warranty	5-year

APPROVALS AND LISTINGS

DIMENSIONAL DRAWING (IN)



CONNECTORS (Sold Separately)

AL-120-CON	120° Connector	
AL-L-CON	90° Connector	
AL-T-CON	T Connector	
AL-X-CON	X Connector	



NOTE: All Connectors require Connection Kits (AL-C-KIT-BK). Please refer to the connector product sheets to learn more.

ELECTRICAL

Wattage	20W
Voltage	120-347V
Current	0.167A
Surge Protection	2kV
Auxiliary Output	N/A
Power Factor	>0.9
THD	>20%
Operating Temp	-40°C to 55°C

CONSTRUCTION

Power Cord	31.5"
Housing	Aluminum
Finish Colour	White
Lens	Polycarbonate
IP Rating	IP20 (Damp Location)

DIMENSIONS AND WEIGHTS

Product Dimensions	24" x 2.8" x 3.3"
Fixture Weight	3.96 lbs
Carton Qty	1
Carton Gross Weight	4.2 lbs
Carton Dimensions	24.8" x 3" x 3.7"
Master Carton Qty	6
Master Carton Gross Weight	28.9 lbs
Master Carton Dimensions	25.4" x 11.8" x 6.9"

KITS AND MOUNTING (Sold Separately)

AL-C-KIT	Connection Kit
AL-S-KIT	Suspension Kit
AL-WM-KIT	Wall Mount Kit
AL-TB-KIT	T Bar Mounting Kit
AL2-MR-KIT	Mud-In Recessed Kit
AL2-R-KIT	Recessed Kit
AL2-L-KIT	Louver Kit

HEAD OFFICE: 8 - 540 Jamieson Pkwy, Cambridge, ON, N3C 0G5 | orders@csc-led.com | (519) 880 - 9833

