

CP03 Canopy Lights

Power Selectable | Colour Selectable | 120-347V

The successor to our best-selling CP02 Canopy Lights!

Ideal for parking structures, pool areas, gas stations, canopies, and more.
Suitable for damp/wet locations or wherever a high impact-resistant fixture is required.

6kV Surge Protection
0-10V dimming



Colour Selectable
3000K / 4000K / 5000K

Power Selectable
20W / 30W / 40W

White Powder
Coat Finish



Faceted Polycarbonate Lens
for Superior Glare Control,
Fire and Vandal Resistance

Dropped Lens for
Improved Beam Angle
allows for wider
spacing of luminaires

Universal 120-347V Input

TECHNICAL DATA



LIGHT SPECIFICATIONS

Efficacy	123.36 lm/W
CCT	3000K / 4000K / 5000K
CRI	83
Beam Angle	110°
Dimmable	0-10V
L70 Life	54,000 hrs
Warranty	5-year

	3000K	4000K	5000K
40W	4889 lm	5393 lm	5374 lm
30W	4288 lm	4675 lm	4634 lm
20W	2892 lm	3101 lm	3119 lm

APPROVALS & LISTINGS

cUL	E482965
DLC Premium	S-ET054C

DIMENSIONS AND WEIGHTS

Fixture Weight	3.89 lbs
Fixture Dimensions	8.03 x 8.03 x 3.67 in
Carton Qty	1
Carton Weight	4.91 lbs
Carton Dimensions	10.16 x 10.24 x 5.83 in
Master Carton Qty	2
Master Carton Weight	11.08 lbs
Master Carton Dimensions	12.28 x 10.75 x 11.02 in

ELECTRICAL

Wattage	20W / 30W / 40W
Voltage	120-347V
Current	0.45A
Surge Protection	6kV
Auxiliary Output	12V
Power Factor	0.9
THD	15%
Operating Temp	-30 to 45°C

CONSTRUCTION

Cord Whip	5.9"
Housing	Aluminum Alloy
Lens	Polycarbonate
Finish	Powder Coated
Finish Colour	White
IP Rating	IP65

ACCESSORIES (Ordered Separately)

Microwave Motion Sensor	MS04-MW-HW-DC
Remote*	HB7B-REMOTE

*HB7B-REMOTE is **required** for the MS04-MW-HW-DC to function

DIMENSIONAL DRAWINGS (IN)

