

# CWP04 Wall Pack

120W | Colour Tunable | 120-347V



Ideal for entryway and exterior security lighting

Easy installation and maintenance with colour temperature and voltage options

Built-in Photocell  
(can be bypassed with switch)

120-347V Driver  
with 6kV surge protection

Instant Start, Soft,  
Uniform Light



Colour Tunable  
3000K/4000K/5000K

Durable Die-Cast  
Aluminum Housing

Borosilicate  
Glass Lens

Optional Accessories (sold separately):  
Wireguard, Visor, Motion Sensor, Remote



CWP04-WG



CWP04-VISOR



HB01DMS-C



HB01R

## TECHNICAL DATA




### LIGHT SPECIFICATIONS

Lumens	16,942 lm
Efficacy	136.7 lm/W
CCT	Tunable 30K/40K/50K
CRI	80
Dimmable	0-10V
L70 Life	50,000 hrs
Warranty	10-year


### APPROVALS AND LISTINGS

cUL	E482965
DLC	PLO3IOL9JJ2U

### ILLUMINANCE AT A DISTANCE



### ISOCANDELA PLOT



### ELECTRICAL

Wattage	120W
Voltage	120-347V
Power Factor	0.9
THD	15%
Operating Temp	-40 to 50°C

### CONSTRUCTION

Housing	Die-Cast Aluminum
Cover	Borosilicate Glass
Finish	Bronze
IP Rating	IP65
Net Weight	3.5 kg
Gross Weight	4.5 kg
Carton Qty	1
Carton Dimensions	397 x 297 x 250 mm

### ACCESSORIES (Ordered Separately)

Visor	CWP04-VISOR
Motion Sensor	HB01DMS-C
Remote	HB01R
Wireguard	CWP04-WG

**Note:** HB01R (remote) is **required** for HB01DMS-C (motion sensor)

### DIMENSIONS

