

# Mini Flood Light

20W / 30W / 50W | 3CCT | 120-347V

Meet the successor to our best-selling FLM Mini Flood Lights!  
Ideal for landscaping, patio, and security lighting, signs and building facades  
Excellent replacement for quartz halogen fixtures

Die-Cast  
Aluminum Housing  
with cooling fins for  
superior heat dissipation



Power Selectable  
20W / 30W / 50W

Built-in Photocell

44 LED Chips  
for even illumination

19.7" Cord Whip

High-Impact  
Polycarbonate  
Lens/Optics

Complete With  
Yoke Mount  
interchangeable mounting  
options sold separately



Colour Selectable  
3000K / 4000K / 5000K

Rugged Polyester  
Powder Coat Finish  
(Bronze)

## TECHNICAL DATA



### LIGHT SPECIFICATIONS

Lumens	6,347 lm
Efficacy	126.5 lm/W
CCT	3000K/4000K/5000K
Distribution	NEMA 7x7
CRI	82
Dimmable	0-10V
L70 Life	> 54,000 hrs
Warranty	10-year

LUMEN OUTPUT			
	3000K	4000K	5000K
20W	3,186 lm	3,315 lm	3,295 lm
30W	4,535 lm	4,782 lm	4,706 lm
50W	6,347 lm	6,883 lm	6,801 lm

### APPROVALS AND LISTINGS

cUL	E482965
DLC	S-Y1BN2H

### ACCESSORIES (SOLD SEPARATELY)

Knuckle Mount	FLM02-KN
Slip Fitter	FL-SF01-BZ
Pole Mount	FL-PM01-BZ
Multi Mount	FL-MM01-BZ
Ratchet Yoke Mount	FLM02-BKT-SM

**NOTE:** FLM02-BKT-SM is **REQUIRED** in order to use the Pole Mount, Slip Fitter, and Multi Mount.

### ELECTRICAL

Wattage	20W / 30W / 50W
Voltage	120-347V
Current	0.55A
Surge Protection	2.5kV
Auxiliary Output	N/A
Power Factor	0.9
THD	15%
Operating Temp	-30°C to 45°C

### CONSTRUCTION

Cord Whip	19.7"
Housing	Die-Cast Aluminum
Finish	Polyester Powder Coat
Finish Colour	Bronze
IP Rating	IP65

### DIMENSIONS

Fixture Weight	2.42 lbs
Fixture Dimensions	8" x 1.8" x 7.2"
Carton Qty	1
Carton Weight	2.86 lbs
Carton Dimensions	9.3" x 2.8" x 11.2"
Master Carton Qty	8
Master Carton Weight	24.86 lbs
Master Carton Dimensions	19.2" x 11.8" x 12"

### ILLUMINANCE AT A DISTANCE

