

Mini Flood Light

55W / 70W / 80W | 3CCT | 120-347V

Meet the successor to our best-selling FLM Mini Flood Lights!
Ideal for landscaping, patio, and security lighting, signs and building facades
Excellent replacement for quartz halogen fixtures

Die-Cast
Aluminum Housing
with cooling fins for
superior heat dissipation



Power Selectable
55W / 70W / 80W

Built-in Photocell

64 LED Chips
for even illumination

19.7" Cord Whip

High-Impact
Polycarbonate
Lens/Optics

Complete With
Yoke Mount
interchangeable mounting
options sold separately



Colour Selectable
3000K / 4000K / 5000K

Rugged Polyester
Powder Coat Finish
(Bronze)

TECHNICAL DATA



LIGHT SPECIFICATIONS

Lumens	10,326 lm
Efficacy	128.3 lm/W
CCT	3000K/4000K/5000K
Distribution	NEMA 7x7
CRI	82
Dimmable	0-10V
L70 Life	> 54,000 hrs
Warranty	10-year

LUMEN OUTPUT			
	3000K	4000K	5000K
55W	8,411 lm	9,002 lm	8,443 lm
70W	9,569 lm	10,462 lm	10,031 lm
80W	10,326 lm	11,270 lm	11,057 lm

APPROVALS AND LISTINGS

cUL	E482965
DLC	S-YMB16N

ACCESSORIES (SOLD SEPARATELY)

Knuckle Mount	FLM02-KN
Slip Fitter	FL-SF01-BZ
Pole Mount	FL-PM01-BZ
Multi Mount	FL-MM01-BZ
Ratchet Yoke Mount	FLM02-BKT-LG

NOTE: FLM02-BKT-LG is **REQUIRED** in order to use the Pole Mount, Slip Fitter, and Multi Mount.

ELECTRICAL

Wattage	55W / 70W / 80W
Voltage	120-347V
Current	0.7A
Surge Protection	2.5kV
Auxiliary Output	N/A
Power Factor	0.9
THD	15%
Operating Temp	-30°C to 45°C

CONSTRUCTION

Cord Whip	19.7"
Housing	Die-Cast Aluminum
Finish	Polyester Powder Coat
Finish Colour	Bronze
IP Rating	IP65

DIMENSIONS

Fixture Weight	3.3 lbs
Fixture Dimensions	9.37" x 1.97" x 8.07"
Carton Qty	1
Carton Weight	3.96 lbs
Carton Dimensions	10.8" x 3" x 12.2"
Master Carton Qty	6
Master Carton Weight	25.3 lbs
Master Carton Dimensions	18.5" x 12.8" x 11.6"

ILLUMINANCE AT A DISTANCE

