

# WPX Wall Pack

50W | Colour Selectable | 120-347V

The most versatile architectural wall pack in Canada  
Ideal for outdoor wall-mount applications such as commercial,  
industrial, retail, or hospitality buildings

Type 3 Distribution Optics Standard

Type 2 and Type 4 options available

1/2" NPT Entry  
on all sides



Colour Selectable  
3000K/4000K/5000K

120-347V Driver  
with 6KV  
surge protection

Durable Die-Cast  
Aluminum Housing



## TECHNICAL DATA



### LIGHT SPECIFICATIONS

Lumens	6,343 lm
Efficacy	127 lm/W
CCT	3000K / 4000K / 5000K
CRI	73
Dimmable	0-10V
L70 Life	50,000 hrs
Warranty	10-year

### APPROVALS AND LISTINGS

cETL	5018387
------	---------

### ACCESSORIES (Ordered Separately)

Visor	WPX-VISOR-S-WH
Type 2 Optics	WPX-T2S
Type 4 Optics	WPX-T4S

### ILLUMINANCE AT A DISTANCE



### ELECTRICAL

Wattage	50W
Voltage	120-347V
Power Factor	0.9
Current	0.68A
THD	16%
Operating Temp	-30 to 45°C

### CONSTRUCTION

Housing	Die-Cast Aluminum
Cover	Polycarbonate
Finish	Power Coat
Finish Colour	White
IP Rating	IP65

### DIMENSIONS & WEIGHTS

Fixture Weight	3.5 lbs
Fixture Dimensions	9.8 x 6.7 x 8.7 in
Carton Qty	1
Carton Weight	3.5 lbs
Carton Dimensions	10.2 x 7.9 x 10.2 in

### DIMENSIONS

