

INSTALLATION INSTRUCTIONS

Item#1721-xxx (New 2024/06/11)

READ AND SAVE THESE INSTRUCTIONS

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DU DISJONCTEUR.

MOUNTING THE FIXTURE (Fig.1)

1. Shut off power at the fuse box or circuit breaker box and remove the old fixture including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts in a clear area. Take care not to misplace any small parts necessary for installation.
3. Determine desired location for installing fixture.
4. Place backplate (A) against wall at desired position. Hook on backplate (A) should be pointing up. Ensure backplate (A) is level. Mark on the wall the location of each hole in the backplate (A). Place backplate (A) aside.
5. Pre-drill appropriate size holes for plastic anchor (B) and insert plastic anchor (B) into wall.
6. Place backplate (A) on wall. Align holes in backplate (A) with plastic anchors (B). Secure back plate (A) to wall using wood screws (C) and plastic anchors (B).
7. Lower shade (D) down over fixture body (E). Place bracket on top of shade (D) onto bracket on fixture body (E).
8. Align holes in bracket on shade (D) with holes on fixture body (E). Tighten thumb screws (F) to secure shade (D) in place. DO NOT over tighten.
9. Wrap cord around hook on backplate (A). Be twined or knotted to fix and ensure plug will reach wall outlet.
10. Install (1) one medium base bulb up to 100 watts each or CFL or LED equivalent (Not included), in accordance with the fixture specification — **DO NOT EXCEED THE MAXIMUM WATTAGE RATING! (NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**.
11. Insert plug into electrical outlet.

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.

Fig. 1

Shade# SH1721

-Plastic Anchor x2
-Wood Screw x2

