


### adorne Collection adorne® 15A Two-Gang Pop-Out Outlet, White Part No. ARPTR152GW2



The cleverest way to add power and style, the Pop-Out Outlet extends to offer 3-plug access, then uniquely disappears back into the wall with a simple push when not in use. Made exclusively for use with screwless Wall Plates from the adorne® Collection, sold separately.

# Features & Benefits

For complete installation, device must be paired with an <u>adorne®</u> <u>screwless Wall Plate</u> (not included). Available in a range of contemporary colors and stunning finishes.	Perfect anywhere you'd like to hide outlets when not in use, for added style and safety.
Provides additional power with 3-plug access when extended from wall.	Disappears back into the wall with a simple push when not needed.
Installs easily in as little as 15 minutes.	Comes with a special frame for mounting and requires a deep electrical outlet (22.5 cubic inches). No new wires required for typical installation.
Protects children with a patented tamper-resistant shutter system that prevents improper insertion of foreign objects, complete with "invisi-shutters" for an invisible effect	More color options available to fit any style, including finishes to match current hardware and lighting trends.

**Specifications** 

"invisi-shutters" for an invisible effect.

#### General Info

Product Line	Pass & Seymour	Color	White
Finish	Matte	UPC Number	786776178623
Country Of Origin	China	Number of Receptacles	3
Features	Pop-Out	Outlet Type	Residential, Indoor, Pop-Out, Tamper-Resistant
Application Sector	Residential	Standard	CULUS
Warranty Type	Limited Lifetime Warranty	Туре	Outlet

## Additional Information

Prop 65 Warning Required No

### Technical Information

Phase	Single	Connection	Side and Back Wire
Number of Wires	3	Number of Gangs	1
Amperage	15 A	Number of Poles	Double Pole
Wire Size	#14 - #10 AWG	Indoor/Outdoor	Indoor
NEMA Configuration Code	5-15R	Mounting Type	Box
Voltage	125 VAC	Connection Type	Internal Pressure Plates
Environmental Conditions	95 (relative humidity, non- condensing)		