Installer-Friendly Features





Rear stabilizer legs

- Rest against opposing wallboard.
- Control the depth that a box can flex.
- Maintain device rigidity during plug insertion.
- Heavy cross section minimizes wallboard damage.

Side stabilizer tabs

- Keep box from flexing out when plug is removed abruptly.
- Permits use of phantom studs.





Height sight

Centers box on your reference mark.

Bracket countersink

Allows #8 waferhead or sheet rock screws with minimal wallboard bow.

Box levelers

Automatically align box at right angle to stud.

For additional technical or application-specific information, call 800-223-4185 or visit our website at www.legrand.us/passandseymour. We're eager to put our expertise to work for vou.

Legrand/Pass & Seymour

P.O. Box 4822 Syracuse, NY 13221-4822 800-776-4035 www.legrand.us/passandseymour

PRODUCT OFFERING HIGHLIGHTS **INCLUDING NEW PRODUCTS AND FEATURES SPRING 2006**

P&S Boxes

Distributed by:

The original Quick/Click®

- Unique, labor-saving design secures device quickly and easily.
- Simply push in and turn the screw one turn.
- Does not strip when over-torqued.



North America Headquarters

60 Woodlawn Street West Hartford, CT 06110 Phone: 1.877.BY.LEGRAND (295.3472) www.legrand.us

Legrand Canada

570 Applewood Crescent Vaughan, ON, L4K 4B4 Phone: 905.738.9195 www.legrand.ca

Pass & Seymour

designed to be better.

Contractor-inspired innovative solutions



Wall Boxes

New Construction

- Quick/Click® feature* secures device quickly and easily. Does not strip when over-torqued.
- Largest box volumes in class.
- Rear stabilizer legs and side stabilizer tab.
- Height sight, bracket countersink, and box levelers.





S3-54-RAC*

S4-68-RAC*

Old Work

S2-35-RAC*

- Quick/Click® feature* secures device quickly and easily. Does not strip when over-torqued.
- Metal swing brackets permit installation of box in wall with 1-1/4" thick wallboard down to 1/8" thick paneling.



Range & Dryer Boxes

- Factory-installed, internal metallic wire clamp provides dependable strain relief.
- Large cable entry accommodates up to #6 gauge copper or aluminum wire.
- Rear stabilizer legs and side stabilizer tab.
- Height sight, bracket countersink, and box levelers.
- Large 42 cubic inch volume.



4" Square Junction Boxes

- Two factory-installed #8 screws for easy mud ring installation (accepts standard P&S mud rings RC1, RC2. or 4SBC).
- Height sight and bracket countersink.
- Shallow 1/4" depth ideal for masonry-furring strip style walls.



S44-18-BAC

Extension Rings

A box that is set back too far? No problem! Use a set of extension rings that allow trim-out adjustment.

- 1/4" thick.
- Stackable for any depth.
- Can be modified to accommodate three- or four-gang applications.



Low-Voltage **Brackets & Divider**

- Available in single, 2- and 3-gang, new construction and old work style.
- Old work style has unique alignment feature and metal swing brackets.
- Robust design with spacious openings.



- Available in single, 2-gang and round, low-voltage, line voltage and dual-voltage.
- Products suitable for wood or concrete sub-floors.
- Nickel, aluminum or brass finish plates.
- Scrub-water compliant.

Floor Boxes



Ceiling Boxes

Nail-On & Direct Mount Boxes

- UL-Listed for fan and fixture support.
- Dual mounting accommodates either 2.75" or 3.5".
- Screw lock on direct mount boxes holds screws in box until needed so there's no lost hardware — and away from spiral saws so there are no broken bits.







S1-16-FAN S1-09-FAN

Metallic Ceiling Boxes & Braces

- Exclusive rotating dual supports for fan and fixtures.
- Broadest line available with convenient top and side knockouts.



^{*}Quick/Click feature on catalog numbers beginning with "S" only.