



Isla 24-in Ceiling Fan

Comments	
	- 1

Model	Light Kit	Color Temperature	Control	CFM (High)	Motor	Included Downrod
CF41424-5CCT CF41424-MB/BR-5CCT CF41424-WH/BR-5CCT	Integrated	5CCT,2700K,3000K,3500K,4000K,5000K	Remote/Smart Control	1303	LV DC	4-1/2" (Additional Sold Separately)







SPECIFICATION DETAILS

Fixture Dimensions	D23-1/8" x H14-3/4"			
Canopy Dimensions	D5-7/8" x H2-5/8"			
Minimum Hang Height	14-3/4"			
Location	Damp			
Diffuser Details	White Polymeric Diffuer			
Dimming Range	100% - 10%			
Illumination Direction	Down			
Light Source/Life	FAN + LED (50,000 hours) 90CRI			
Material	Steel, Rope			
Blade	3 Blades			
Ceiling to Blade Min Distance (Inch)	10.8			
Primary Control	Remote/Smart Control			
Paint Finish	MB01 (MB/BR), WH01 (WH/BR)			
Slopped Ceiling Adaptable	Yes, 20 Deg			
Rod Length	4-1/2" (for different rod length, contact factory)			
Fan Speeds	6 Speed (Reversible: Yes) (200-400 RPM)			
Airflow Efficiency (CFM/WATT)	63			
Shade Details	Rope Shade			
Compliance	ETL Certified: Yes			

WWW.KUZCOLIGHTING.COM

USA: 3035 E. LONE MOUNTAIN ROAD - LAS VEGAS, NV 89081 CANADA: 19054 28TH AVENUE - SURREY, BC V3Z 6M3

Kuzco Lighting reserves the right to modify the design of our products at any time, as part of our ongoing

© 2025 KUZCO LIGHTING. ALL RIGHTS RESERVED

commitment to continuous improvement.

FINISHES







Rope (WH/BR)

^{*} For custom options, contact customer service.