## **LED Linear Pendant**

## LP17905-UNV-010

INSTALLATION SHEET

## START FROM HERE

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- · Prepare everything in a clear area
- · Wear gloves at all time during this installation
- · Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

**Technical Support:** 1-855-855-8926

## Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use ELV (Electronic Low Voltage), TRIAC or 0-10V type of dimmer for dimming application
- 120-277V input

1. Remove fixture from its original package

2. Separate mounting plate (1c) from canopy (2a) by removing canopy screws (2b)

**3.** Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package

**4.** Secure mounting plate (1c) to mounting surface with screws (1g) and anchors (1f)

**5.** To change fixture height, push and hold wire gripper (2g), slide wire to desired length and then release wire gripper (2g) to secure

6. Make proper electrical connections (black to hot "L", white to neutral "N", green to "GND", Dim + to purple, Dim- to gray) with wire nuts (1b) provided in hardware package

 Attach canopy (2a) to mounting plate (1c) with canopy screws (2b)

8. Pull wire through aircraft barrel (3b) and stopper (3d). Secure aircraft barrel (3b) to mounting surface with anchor (3c) and screw (3a). Adjust wire to desired length and secure with set screw (3e). Insert wire gripper (2g) into aircraft barrel (3b) to close

**9.** Fine tone wire length if necessary, by push and hold wire gripper (2g) and then adjust wire to desired length



