



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11221 - 6 Watt LED Bulb; J-Type T3 78mm; 120 Volt; R7S Base; 4000K; Double Ended; 200 Degree Beam Angle



ELECTRICAL

Technology:	LED
Watts:	6W
Volts:	120V
Lumens:	600L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	200
Hours Rated:	15000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Incandescent Equivalent :	40W
HID Equivalent :	75W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Operating Position:	Universal
Candlepower :	70
Power Factor :	0.7
Light Source:	LED
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923112218
Each Quantity:	1
Each Dimensions:	0.20 x 3.70 x 5.51

INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------

PHYSICAL

Base:	Double Ended Recessed Single Contact
Shape:	T3
Finish:	Clear
Lens Finish:	Clear
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 3.07 - MOD: 0.98
Weight (Lbs.):	0.04
Material:	Polycarbonate (PC)
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S11221 - 6 Watt LED Bulb; J-Type T3 78mm; 120 Volt; R7S Base;
4000K; Double Ended; 200 Degree Beam Angle

DIMMER COMPATIBILITY

Leviton	6674
Leviton	66ELV
Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Leviton	DDMX1
Leviton	DSE06-10Z
Eaton	DUL06P-C2
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	IPE04-1L
Leviton	IPL06
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX
Lutron	PD-6WCL
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Lutron	RRD-6CL
Lutron	RRD-PRO

