



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11237** - 5 Watt; JCD LED; Frost; 4000K; G9 Base; 120 Volt



#### ELECTRICAL

|                         |                                                             |
|-------------------------|-------------------------------------------------------------|
| Technology:             | LED                                                         |
| Watts:                  | 5W                                                          |
| Volts:                  | 120V                                                        |
| Lumens:                 | 500L                                                        |
| CRI:                    | 80+                                                         |
| CCT (Kelvins):          | 4000K - Cool White                                          |
| Beam Spread :           | 300                                                         |
| Hours Rated:            | 25000                                                       |
| Dimmable:               | Yes-Dimmable -                                              |
| Dimming Type :          | Forward Phase or Reverse Phase or Phase Selectable or Triac |
| HID Equivalent :        | 40W                                                         |
| Operating Temperature : | -20C (-4F) to +40C (+104F)                                  |
| Power Factor :          | 0.9                                                         |
| Light Source:           | LED                                                         |
| Voltage Type:           | AC Only                                                     |
| Warranty:               | 5-Years                                                     |

#### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923112379       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 1.57 x 1.57 x 2.95 |

#### INFO

|                    |                                                                                                                                                        |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Installation Note: | Not for use in vapor tight fixtures. For proper ventilation, original protective glass shield for halogen lamps should be removed during installation. |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|

#### PHYSICAL

|                   |                              |
|-------------------|------------------------------|
| Base:             | G9 Double Loop               |
| Shape:            | T4                           |
| Finish:           | Frost                        |
| Dimensions (In.): | MOL: 2.13 - MOD: 0.75        |
| Weight (Lbs.):    | 0.06                         |
| Material:         | Ceramic / Polycarbonate (PC) |
| Housing Color:    | White                        |

#### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Damp                              |
| Indoor/Outdoor:             | Indoor                            |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| Enclosure Rating:           | Enclosed Rated Lamp               |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| IP Rating:                  | IP20                              |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S11237** - 5 Watt; JCD LED; Frost; 4000K; G9 Base; 120 Volt

#### DIMMER COMPATIBILITY

|         |            |
|---------|------------|
| Leviton | 6672       |
| Leviton | 6674       |
| Leviton | 66ELV      |
| Satco   | 86/103     |
| Legrand | ADTP703TU  |
| Lutron  | AYCL-153P  |
| Lutron  | AYCL-253P  |
| Lutron  | CTCL-153P  |
| Lutron  | CTRP-253P  |
| Eaton   | DAL06P-C2  |
| Leviton | DDMX1      |
| Leviton | DG6HD      |
| Leviton | DH6HD      |
| Leviton | DL6HD      |
| Leviton | DSE06-10Z  |
| Leviton | DSL06      |
| Leviton | DSL06-1LZ  |
| Leviton | DSM10      |
| Lutron  | DVCL-153P  |
| Lutron  | DVCL-253P  |
| Lutron  | DVRP-253P  |
| Leviton | DW6HD      |
| Leviton | DZ6HD      |
| Lutron  | HQRA-PRO   |
| Lutron  | HQRD-10D   |
| Lutron  | HQRD-10NBD |

|                |             |
|----------------|-------------|
| <b>Lutron</b>  | HQRD-6ND    |
| <b>Lutron</b>  | HQRD-HN6BRL |
| <b>Lutron</b>  | HQRD-PRO    |
| <b>Lutron</b>  | HRST-PRO-N  |
| <b>Leviton</b> | IPE04-1L    |
| <b>Leviton</b> | IPL06       |
| <b>Lutron</b>  | LECL-153P   |
| <b>Lutron</b>  | MA-PRO      |
| <b>Lutron</b>  | MACL-153M   |
| <b>Lutron</b>  | MACL-LFQ    |
| <b>Lutron</b>  | MRF2S-6ELV  |
| <b>Lutron</b>  | MSCL-OP153M |
| <b>Lutron</b>  | NTCL-250    |
| <b>Lutron</b>  | NTRP-250    |
| <b>Lutron</b>  | PD-10NXD    |
| <b>Lutron</b>  | PD-6WCL     |
| <b>Lutron</b>  | RCL-153PNL  |
| <b>Eaton</b>   | RF9640-ND   |
| <b>Legrand</b> | RHCL450PTC  |
| <b>Leviton</b> | RNL06-10Z   |
| <b>Lutron</b>  | RRD-10D     |
| <b>Lutron</b>  | RRD-6CL     |
| <b>Lutron</b>  | RRD-6ND     |
| <b>Lutron</b>  | RRD-H6BRL   |
| <b>Lutron</b>  | RRD-PRO     |
| <b>Lutron</b>  | RRST-PRO-N  |
| <b>Satco</b>   | S11268      |
| <b>Eaton</b>   | SAL06P      |

|                |            |
|----------------|------------|
| <b>Lutron</b>  | SCL-153P   |
| <b>Lutron</b>  | ST-PRO-N   |
| <b>Lutron</b>  | STCL-153M  |
| <b>Eaton</b>   | SUF7       |
| <b>Eaton</b>   | TAL06P-C2  |
| <b>Lutron</b>  | TGCL-153PH |
| <b>Leviton</b> | TSL06      |
| <b>Leviton</b> | TSM10      |
| <b>Lutron</b>  | TTCL-100H  |
| <b>Eaton</b>   | VSUL06D    |