



Project/Job Name:

Location:

Fixture Type:

Notes:

S11333 - 7.5 Watt; BR30 LED; 2700K; Medium base; 105 deg. Beam Angle; 120 Volt; 2-pack



ELECTRICAL

Technology:	LED
Watts:	7.5W
Volts:	120V
Lumens:	650L
CRI:	90+
Rg Value :	67
CCT (Kelvins):	2700K - Warm White
Beam Spread :	105
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	65W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Candlepower :	220
Power Factor :	0.92
Light Source:	LED
CBCP :	220
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923113338
Each Quantity:	1
Each Dimensions:	7.68 x 3.86 x 5.51

PHYSICAL

Base:	Medium
Shape:	BR30
Finish:	Gray
Lens Finish:	Gray
Lens Material:	Plastic (PS)
Dimensions (In.):	MOL: 5.157 - MOD: 3.74
Weight (Lbs.):	0.194
Material:	Metal / Plastic / Electronic Components
Housing Color:	Gray
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S11333 - 7.5 Watt; BR30 LED; 2700K; Medium base; 105 deg. Beam Angle; 120 Volt; 2-pack

DIMMER COMPATIBILITY

Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Eaton	DALo6P-C2
Leviton	DDL06
Leviton	DDMX1
Leviton	DSL06-1LZ
Eaton	DULO6P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Lutron	RRD-6CL
Satco	S11268
Satco	S11270
Eaton	SALO6P

Eaton	SUF7
-------	------

Eaton	TALo6P-C2
Eaton	VSULo6D