



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11335** - 6.5 Watt; MR16 LED; 3000K; GU5.3 base; 25 deg. Beam Angle; 12 Volt



### ELECTRICAL

|                           |                                                                          |
|---------------------------|--------------------------------------------------------------------------|
| Technology:               | LED                                                                      |
| Watts:                    | 6.5W                                                                     |
| Volts:                    | 12V                                                                      |
| Lumens:                   | 450L                                                                     |
| CRI:                      | 90+                                                                      |
| Rg Value :                | 64                                                                       |
| CCT (Kelvins):            | 3000K - Warm White                                                       |
| Beam Spread :             | 25                                                                       |
| Hours Rated:              | 25000                                                                    |
| Dimmable:                 | Yes-Dimmable - Check the transformer/driver MFG for dimmer compatibility |
| Dimmable Down To %:       | 100 to 10 percent                                                        |
| Dimming Type :            | Forward Phase or Reverse Phase or Phase Selectable                       |
| Incandescent Equivalent : | 50W                                                                      |
| Operating Temperature :   | -25C (-13F) to +45C (+113F)                                              |
| Candlepower :             | 1700                                                                     |
| Power Factor :            | 0.93                                                                     |
| Light Source:             | LED                                                                      |
| CBCP :                    | 1700                                                                     |
| Voltage Type:             | AC/DC                                                                    |
| Warranty:                 | 5-Years                                                                  |

### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923113352       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 1.97 x 1.97 x 2.56 |

### PHYSICAL

|                   |                                         |
|-------------------|-----------------------------------------|
| Base:             | Bi Pin GU5.3                            |
| Shape:            | MR16                                    |
| Finish:           | Gray                                    |
| Lens Finish:      | Gray                                    |
| Lens Material:    | Plastic (PS)                            |
| Dimensions (In.): | MOL: 1.772 - MOD: 1.969                 |
| Weight (Lbs.):    | 0.08                                    |
| Material:         | Metal / Plastic / Electronic Components |
| Housing Color:    | Gray                                    |
| Lensed:           | Lensed Lamp                             |

### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Damp                              |
| Indoor/Outdoor:             | Indoor                            |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| Enclosure Rating:           | Enclosed Rated Lamp               |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S11335** - 6.5 Watt; MR16 LED; 3000K; GU5.3 base; 25 deg. Beam Angle; 12 Volt

#### DIMMER COMPATIBILITY

|         |            |
|---------|------------|
| Leviton | 66ELV      |
| Lutron  | CTRP-253P  |
| Eaton   | DALo6P-C2  |
| Leviton | DDMX1      |
| Eaton   | DULo6P-C2  |
| Lutron  | DVRP-253P  |
| Leviton | DW6HD      |
| Lutron  | MA-PRO     |
| Lutron  | NTRP-250   |
| Eaton   | RF9640-ND  |
| Legrand | RH703PTUTC |
| Legrand | RHCL450PTC |
| Eaton   | SUF7       |
| Eaton   | VSULo6D    |